

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

Point for the standard W 1/16 sec. cor. of sec. 35.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap, from which:

A Douglas fir, 21 ins. diam., bears N.60°E., 53 lks. dist. mkd. W 1/16 S35 SC BT.

A Douglas fir, 11 ins. diam., bears N.71 ¾°W., 17 lks. dist. mkd. X at breast height and BT at the base.

Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.

Description of corner evidence found:


Found a 3" BLM brass capped pipe, cap marked per diagram , 8" above the ground, no stones, from which:

A fir, 12" diam., bears N.71°08'W., 11.40', with a 8" x 2" blaze, scribed "BT".

A fir, 19" diam., bears N.59°37'E., 34.98', with a 15" x 4" blaze (not legible).

Description of monument and accessories I established to perpetuate the original location of this corner:

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.



UNION COUNTY
SURVEYOR
Date Received 10/28/98
Date Filed 10/31/98
By R. ROBINSON, Deputy
File No. 100-1490R

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Ronald E. Stoll 9/98
OREGON
JULY 15, 1993
RONALD E. STOLL
2059

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-18

History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

Point for the standard W 1/16 sec. cor. of sec. 35.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap, from which:

- A Douglas fir, 21 ins. diam., bears N.60°E., 53 lks. dist. mkd. W 1/16 S35 SC BT.
- A Douglas fir, 11 ins. diam., bears N.71 3/4°W., 17 lks. dist. mkd. X at breast height and BT at the base.

Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.


Description of corner evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, 8" above the ground, no stones, from which:

- A fir, 12" diam., bears N.71°08'W., 11.40', with a 8" x 2" blaze, scribed "BT".
- A fir, 19" diam., bears N.59°37'E., 34.98', with a 15" x 4" blaze (not legible).

Description of monument and accessories I established to perpetuate the original location of this corner:

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
 WITNESS TO MONUMENT: DAVID SUTHERLAND
 BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
 BASIS OF BEARING WAS GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.



UNION COUNTY SURVEYOR

Date Received 1/4/06

Date Filed 9/9/06

By R. ROBINSON DEPUTY

File No. 024-2006R

REGISTERED PROFESSIONAL LAND SURVEYOR

Ronald E. Stoll 6/04

OREGON
 JULY 15, 1983
RONALD E. STOLL
 2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ____ day of _____, 20____.

By _____
 (COUNTY OFFICIAL) (DEPUTY)

BZ

Dependent Resurvey of the South Boundary
(First Standard Parallel South),
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	From this point, the corner of wire fences, extending S. and W., bears N. $25\frac{1}{4}^{\circ}$ E., 0.850 chs. dist.
	Descend steep W. slope.
12.00	Creek, 3 lks. wide, course N. 20° W.
15.00	Spur, slopes N.; desc. NW. slope.
27.50	Creek, 3 lks. wide, course S. 70° W.; desc. along broken S. slope.
39.650	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, $4\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	SC T 5 S R 41 E <u> $\frac{1}{4}$ S 35</u> 1991
	from which
	A ponderosa pine, 13 ins. diam., bears N. $46\frac{1}{2}^{\circ}$ E., 88 lks. dist., mkd. $\frac{1}{4}$ S35 SC BT.
	A ponderosa pine, 27 ins. diam., bears N. $15\frac{1}{4}^{\circ}$ W., 89 lks. dist., mkd. X at breast height and BT at the base.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	The corner is located on a rocky SW. slope, 70 lks. S. of a barbed wire fence, extending E. and W.
	Descend steep SW. slope.
44.50	Creek, 3 lks. wide, course NW.; asc. gradually along NE. slope.
59.475	Point for the standard W $1/16$ sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	SC W $1/16$ <u> S 35</u> 1991
	from which
	A Douglas fir, 21 ins. diam., bears N. 60° E., 53 lks. dist., mkd. W $1/16$ S35 SC BT.
	A Douglas fir, 11 ins. diam., bears N. $71\frac{1}{4}^{\circ}$ W., 17 lks. dist., mkd. X at breast height and BT at the base.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By



File No.

176-2013R

Dependent Resurvey of the South Boundary
(First Standard Parallel South),
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located 25 lks. S. of a barbed wire fence, extending E. and W.</p> <p>Descend NW. slope.</p>
79.300	<p>The standard cor. of secs. 34 and 35, monumented with the original slate stone, 14 x 10 x 5 ins., loosely set 3 ins. in the ground, mkd. SC on the S. face, and with 6 grooves on the N., 2 grooves on the E., and 4 grooves on the W. edges, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A root hole with loose pine roots within, bears N. 35° E., 95 lks. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>T 5 S R 41 E</p> <p><u>S 34 S 35</u></p> <p>1991</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 28½° E., 11 lks. dist., mkd. T5S R41E S35 SC BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 82° W., 11 lks. dist., mkd. T5S R41E S34 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p> <p>The corner is located 12 lks. S. of a barbed wire fence, extending E. and W.</p> <hr/> <p>S. 89° 07' 30" W., on the S. bdy. of sec. 34.</p> <p>Over gradual S. slope along wire fence.</p>
11.910	<p>From this point, the corner of wire fences extending E. and S., bears North, 0.017 chs. dist.; desc. SW. slope.</p>
16.25	<p>Oregon State Highway No. 203, paved, 40 lks. wide, bears N. 10° W. and S. 10° E.; asc. gradually over pasture.</p>
30.00	<p>Leave pasture; asc. steep NE. slope through medium timber and undergrowth.</p>
40.485	<p>The standard ¼ sec. cor. of sec. 34, monumented with the original slate stone, 24 x 10 x 6 ins., loosely set 3 ins. in the ground, mkd. ¼ on the N. face, from which the remains of an original bearing tree:</p>

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By



File No.

176-2013R