


CERTIFIED RECORD OF LAND CORNER MONUMENTATION



History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

Point for the standard ¼ sec. cor of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins in the ground, to solid rock, and in a mound of stone, 4½ ft. base, to top, with brass cap, from which:

A ponderosa pine, 13 ins. diam., bears N.46½°E., 88 lks. dist. mkd. ¼ S35 SC BT.

A ponderosa pine, 27 ins. diam., bears N.15¼°W., 89 lks. dist. mkd. X at breast height and BT at the base.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Description of corner evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, in a 5' diam. mound of stones to cap, from which:

A fir, 10" diam., bears N.46°30'E., 58.22' with a 20" x 4" blaze, scribing not legible

A ponderosa pine, 24" diam., bears N.15°27'W., 59.09', with a 6" x 5" blaze, scribed "BT".

A ponderosa pine, 12" diam., bears S.55°07'E., 11.15', with a blaze.

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 9" diam., bears S.78°01'W., 25.66', with a 7" x 4" blaze, scribed "BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY

WITNESS TO MONUMENT: DAVID SUTHERLAND

BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.

BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

RECORDED
SURVEYOR
Date Received 10/28/98
Date Filed 10/31/98
By R. ROBINSON, DEPUTY
File No. 099-1998R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

W. A. Stoll 9/98

OREGON
JULY 13, 1903
RONALD E. STOLL
2058

Office of _____ State of _____ I hereby certify that the within instrument was filed in this office for record on the _____ day of _____, 19____

_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

BY

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-19

History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

Point for the standard 1/4 sec. cor of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins in the ground, to solid rock, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap, from which:

- A ponderosa pine, 13 ins. diam., bears N.46 1/2°E., 88 lks. dist. mkd. 1/4 S35 SC BT.
- A ponderosa pine, 27 ins. diam., bears N.15 1/4°W., 89 lks. dist. mkd. X at breast height and BT at the base.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Description of corner evidence found:


Found a 3" BLM brass capped pipe, cap marked per diagram, in a 5' diam. mound of stones to cap, from which:

- A ponderosa pine, 24" diam., bears N.15°27'W., 59.09', with a 6" x 5" blaze, scribed "BT".
- A pine, 12" diam., bears N.46°30'E., 58.22', with a 20"x4" blaze, scribing not legible

Description of monument and accessories I established to perpetuate the original location of this corner:

- A fir, 9" diam., bears S.78°01'E., 25.66', with a 7" x 4" blaze, scribed "BT".
- A fir, 10" diam., bears S.55°07'E., 11.15', with a 20" x 4" blaze scribed "BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
 WITNESS TO MONUMENT: DAVID SUTHERLAND
 BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
 BASIS OF BEARING WAS GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.



UNION COUNTY SURVEYOR

Date Received 1/4/06

Date Filed 9/9/06

By R. ROBINSON DEPUTY

File No. 023-2006R

REGISTERED PROFESSIONAL LAND SURVEYOR

M & Stoll 10/06

OREGON
 JULY 15, 1988
 RONALD E. STOLL
 2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ___ day of _____, 20____.
 _____ By _____
 (COUNTY OFFICIAL) (DEPUTY)
 BY

Dependent Resurvey of the South Boundary
 (First Standard Parallel South),
 T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>From this point, the corner of wire fences, extending S. and W., bears N. 25¼° E., 0.850 chs. dist.</p> <p>Descend steep W. slope.</p>
12.00	Creek, 3 lks. wide, course N. 20° W.
15.00	Spur, slopes N.; desc. NW. slope.
27.50	Creek, 3 lks. wide, course S. 70° W.; desc. along broken S. slope.
39.650	<p>Point for the standard ¼ sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 4½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>T 5 S R 41 E</p> <hr style="width: 50%; margin: 0 auto;"/> <p>¼ S 35</p> <hr style="width: 50%; margin: 0 auto;"/> <p>1991</p> </div> <p>from which</p> <ul style="list-style-type: none"> • A ponderosa pine, 13 ins. diam., bears N. 46½° E., 88 lks. dist., mkd. ¼ S35 SC BT. • A ponderosa pine, 27 ins. diam., bears N. 15¼° W., 89 lks. dist., mkd. X at breast height and BT at the base. <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on a rocky SW. slope, 70 lks. S. of a barbed wire fence, extending E. and W.</p> <p>Descend steep SW. slope.</p>
44.50	Creek, 3 lks. wide, course NW.; asc. gradually along NE. slope.
59.475	<p>Point for the standard W 1/16 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>W 1/16</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 35</p> <hr style="width: 50%; margin: 0 auto;"/> <p>1991</p> </div> <p>from which</p> <ul style="list-style-type: none"> • A Douglas fir, 21 ins. diam., bears N. 60° E., 53 lks. dist., mkd. W 1/16 S35 SC BT. • A Douglas fir, 11 ins. diam., bears N. 71¼° W., 17 lks. dist., mkd. X at breast height and BT at the base.

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>RL Gilman</i>
File No.	177-2013R