


CERTIFIED RECORD OF LAND CORNER MONUMENTATION



History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins in the ground, with brass cap, from which:

A ponderosa pine, 17 ins. diam., bears N.13 ¾°E., 37 lks. dist. mkd. T5S R41E S36 SC BT.

A ponderosa pine, 19 ins. diam., bears N.30 ¾°W., 45 lks. dist. mkd. T5S R41E S35 SC BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Description of evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, 0.2' out of the ground with no stones, from which:

A pine, 19" diam., bears N.81°17'W., 29.24', with a 24" x 4" blaze, hard to read, scribed ".....35 SC BT".

A pine, 18" diam., bears N.36°50'W., 24.72', with a 24" x 3' blaze (not legible).

UNION COUNTY
SURVEYOR
Date Received 10/28/98
Date Filed 10/31/98
by R. ROBINSON DEWITT
File No. 098-1998R

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 7" diam., bears S.80°54'E., 13.64', with a 10" x 4" blaze, scribed "X BT".

A fir, 22" diam., bears S.08°24'W., 32.46', with a 8" x 4" blaze, scribed "BT".


REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Ronald E. Stoll 9/98
OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-21



History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins in the ground, with brass cap, from which:

A ponderosa pine, 17 ins. diam., bears N.13 ¾°E., 37 lks. dist. mkd. T5S R41E S36 SC BT.

A ponderosa pine, 19 ins. diam., bears N.30 ¾°W., 45 lks. dist. mkd. T5S R41E S35 SC BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Description of evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, 0.2' out of the ground with no stones, from which:

A pine, 19" diam., bears N.13°45'E., 24.72', with a 24" x 4" blaze, hard to read, scribed ".....36 SC BT".

A pine, 18" diam., bears N.30°45'W., 29.24', with a 24" x 3' blaze (not legible).

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 7" diam., bears S.30°18'E., 13.64', with a 10" x 4" blaze, scribed "X BT".

A fir, 22" diam., bears S.58°59'W., 32.46', with a 8" x 4" blaze, scribed "BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARING WAS GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY SURVEYOR

Date Received 1/4/06

Date Filed 9/9/06

By R. ROBINSON Deputy

File No. 022-2006R

REGISTERED PROFESSIONAL LAND SURVEYOR

M & State 5/05

OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 20____.

(COUNTY OFFICIAL) (DEPUTY)

BX

Dependent Resurvey of the South Boundary
 (First Standard Parallel South),
 T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS													
	Descend W. slope changing to NW. slope.												
66.00	Along N. edge of road.												
74.00	Spur, slopes NW.; leave road, desc. W. slope.												
79.300	<p>Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">SC</td></tr> <tr><td>T 5 S</td><td>R 41 E</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>from which</p> <p>A ponderosa pine, 17 ins. diam., bears N. 13¾° E., 37 lks. dist., mkd. T5S R41E S36 SC BT.</p> <p>A ponderosa pine, 19 ins. diam., bears N. 30¾° W., 45 lks. dist., mkd. T5S R41E S35 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>	SC		T 5 S	R 41 E	S 35	S 36	1991					
SC													
T 5 S	R 41 E												
S 35	S 36												
1991													
	N. 89° 42' 00" W., on the S. bdy. of sec. 35.												
	Descend broken SW. slope.												
5.50	Spur, slopes SW.; desc. W. slope.												
10.705	<p>Point for the closing cor. of secs. 1 and 2, T. 6 S., R. 41 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 5 S</td><td>R 41 E</td></tr> <tr><td>S 35</td><td></td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>T 6 S</td><td>R 41 E</td></tr> <tr><td colspan="2">CC</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>from which</p> <p>A larch, 14 ins. diam., bears S. 12¼° E., 65 lks. dist., mkd. T6S R41E S1 CC BT.</p> <p>A ponderosa pine, 20 ins. diam., bears S. 4¼° W., 99 lks. dist., mkd. T6S R41E S2 CC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>	T 5 S	R 41 E	S 35		S 2	S 1	T 6 S	R 41 E	CC		1991	
T 5 S	R 41 E												
S 35													
S 2	S 1												
T 6 S	R 41 E												
CC													
1991													

UNION COUNTY SURVEYOR	
Received	3/5/13
Date Filed	3/5/13
By	<i>R. L. G. [Signature]</i>
File No.	178-2013A