

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

39.650 Point for the standard 1/4 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap.

From which:

- A larch, 10 ins. diam., bears N.88 1/2°E., 20 lks. dist. mkd. 1/4 S36 SC BT.
- A ponderosa pine, 14 ins. diam., bears N.60 1/2°W., 37 lks. dist. mkd. 1/4 S36 SC BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Description of corner evidence found:


Found a 3" BLM brass capped pipe, cap marked per diagram, 5" above the ground with no stones, in a wooded area, from which:

- A larch, 10" in diam., bears N.88°50'E., 12.97', scribed "1/4S36SCBT".
- A pine, 14" in diam., bears N.59°16'W., 23.85', scribe unledgible.

Description of monument and accessories I established to perpetuate the original location of this corner:

- A larch, 8" in diam., bears N.19°35'E., 18.06', scribed "1/4S36SCBT".
- A larch, 10" in diam., bears S.18°43'E., 16.68' scribed "1/4S36SCBT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
 WITNESS TO MONUMENT: DAVID SUTHERLAND
 BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
 BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.



UNION COUNTY SHERIFF
Date Received <u>10/23/98</u>
Date Filed <u>10/31/98</u>
By <u>R. Robinson, Deputy</u>
File No. <u>017-1998R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR
<i>RU & Stoll 9/98</i>
OREGON JULY 16, 1933 RONALD E. STOLL 2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

39.650 Point for the standard 1/4 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap.

From which:

- A larch, 10 ins. diam., bears N.88 1/2°E., 20 lks. dist. mkd. 1/4 S36 SC BT.
- A ponderosa pine, 14 ins. diam., bears N.60 1/2°W., 37 lks. dist. mkd. 1/4 S36 SC BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Description of corner evidence found:

Found a 3' BLM brass capped pipe, cap marked per diagram, 5" above the ground with no stones, in a wooded area, from which:


- A larch, 10" in diam., bears N.88°50'E., 12.97', scribed "1/4S36SCBT".
- A pine, 14" in diam., bears N.59°16'W., 23.85', scribing not legible.

Description of monument and accessories I established to perpetuate the original location of this corner:

- A larch, 8" in diam., bears N.19°35'E., 18.06', scribed "1/4S36SCBT".
- A larch, 10" in diam., bears S.18°43'E., 16.68' scribed "1/4S36SCBT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
 WITNESS TO MONUMENT: DAVID SUTHERLAND
 BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
 BASIS OF BEARING WAS GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

Z-23



UNION COUNTY
 SURVEYOR

Date Received 1/4/06
 Date Filed 9/9/06
 By R. ROBINSON, Deputy
 File No. 021-2006R

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

M. Stoll 10/04

OREGON
 JULY 15, 1983
 RONALD E. STOLL
 2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ___ day of _____, 20 ____.
 _____ By _____
 (COUNTY OFFICIAL) (DEPUTY)

BW

Dependent Resurvey of the South Boundary
(First Standard Parallel South),
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS					
11.645	<p>From this point, the original closing cor. of Tps. 6 S., Rs. 41 and 42 E., bears South, 0.280 chs. dist., determined at record bearing and distance from the remains of an original bearing tree:</p> <p>A rotten Douglas fir stump, 25 ins. diam., bears S. 60° W., 23 lks. dist., with scribe marks S2 BT on pitched, detached blaze. Marks on bearing tree coincide with the erroneous description given in the original notes and tree is accepted as the SW. bearing tree.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <p>S 36</p> <table border="1"> <tr> <td>S 1</td> <td>S 6</td> </tr> <tr> <td>R 41 E</td> <td>R 42 E</td> </tr> </table> <p>T 6 S</p> <p>C C</p> <p>1991</p> </div> <p>from which new bearing trees</p> <p>A larch, 10 ins. diam., bears S. 59° E., 21 lks. dist., mkd. T6S R42E S6 CC BT.</p> <p>A lodgepole pine, 8 ins. diam., bears S. 37° W., 21 lks. dist., mkd. T6S R41E S1 CC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend gradually over NE. slope.</p>	S 1	S 6	R 41 E	R 42 E
S 1	S 6				
R 41 E	R 42 E				
35.25	Broad spur, slopes N.; desc. W. slope.				
39.650	<p>Point for the standard ¼ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>T 5 S R 41 E</p> <p>¼ S 36</p> <p>1991</p> </div> <p>from which</p> <p>A larch, 10 ins. diam., bears N. 88½° E., 20 lks. dist., mkd. ¼ S36 SC BT.</p> <p>A ponderosa pine, 14 ins. diam., bears N. 60½° W., 37 lks. dist., mkd. ¼ S36 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>				

UNION COUNTY
SURVEYOR

Date Received 3/5/12

Date Filed 3/5/13

By RL Gillen

File No. 179-2013R