


R-5 T55 R42E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON POST 28" Long set 20" in Ground  
And in a mound of stone 2' Base to Top  
with 5' STEEL Fence Post Along side



ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

- A Fir 8" BRs. N 66 1/2° E 162 LKS, MKD. T55 R42E S 20 BT
- A Fir 16" BRs. S 36 3/4° E 207 LKS, MKD. T55 R42E S 29 BT
- A P. Pine 15" BRs. S 6° W 73 LKS, MKD. T55 R42E S 30 BT
- A P. Pine 8 BRs. N 34 1/4° W 44 1/2 LKS MKD. T55 R42E S 19 BT

Work Done By S. AIBRIGHT Title CADASTRAL SURVEYOR Date 9/30/71 State Registration No. 2111  
or Agency

Certified Cor. Record Prepared? Yes  No  Filed At: \_\_\_\_\_ Date \_\_\_\_\_

REMARKS

Index File No. T. R. M. Tract or Surv. No. Cor. 12  
13

**UNION COUNTY  
SURVEYOR**

---

Date Received \_\_\_\_\_

Date Filed 12-28-87

By G. LANGLITZ DEPUTY

File No. 458-87R

R-5

T5S42R05

## T. 5 S., R. 42 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 42 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350 Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivision, T. 5 S., R. 42 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by James P. Currin,  
Deputy Surveyor, in 1898)

The ½ sec. cor. of secs. 30 and 31, monumented with the original stone, 18 x 12 x 3 ins., firmly set, 10 ins. in the ground, with chisel marks visible on N. face, from which the original bearing trees:

A ponderosa pine, 29 ins. diam., bears N. 8° E.,  
67 lks. dist., with scribe marks S30 visible on  
opened blaze. (Record, N. 5° E.)

A root hole, bears S. 80° E., 15 lks. dist., with  
a down ponderosa pine alongside, 40 ins. diam.,  
with scribe marks ¼ S visible on open blaze.

At the corner point

Set an iron post, 26 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 5 S R 42 E

¼ S 30  
¼ S 31

1971

from which new bearing trees

A ponderosa pine, 16 ins. diam., bears N. 41½° W.,  
86½ lks. dist., mkd. ¼ S30 BT.

A fir, 9 ins. diam., bears S. 55° E., 65 lks.  
dist., mkd. ¼ S31 BT.

Deposit corner stone and set 5 ft. steel fence  
post alongside iron post.

The cor. of secs. 19, 20, 29, and 30, determined at re-  
cord distance from the original bearing trees:

A ponderosa pine, 37 ins. diam., bears N. 86½° E.,  
85 lks. dist., with illegible scribe marks visible  
on open blaze. (Record, N. 81° E.)

UNION COUNTY  
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 394-2013R

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 42 E., Willamette Meridian, Oregon

CHAINS

A ponderosa pine, 41 ins. diam., bears S.  $64\frac{1}{2}^{\circ}$  E.,  
186 lks. dist., with scribe marks T5S R42E S2  
visible on open blaze. (Record, S.  $70^{\circ}$  E.)

A root hole, bears S.  $31^{\circ}$  W., 62 lks. dist., with  
a down ponderosa pine alongside, size indeter-  
minate, with illegible scribe marks visible on  
burned blaze.

A ponderosa pine, 31 ins. diam., bears N.  $66^{\circ}$  W.,  
203 lks. dist., with scribe marks 5S 42 1 B  
visible on open double blaze. (Record, N.  $70^{\circ}$  W.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins.  
in the ground, and in a mound of stone, 2 ft. base, to  
top, with brass cap mkd.

T 5 S R 42 E  
S 19 | S 20  
S 30 | S 29  
1971

from which new bearing trees

A fir, 8 ins. diam., bears N.  $66\frac{1}{2}^{\circ}$  E., 162 lks.  
dist., mkd. T5S R42E S20 BT.

A fir, 16 ins. diam., bears S.  $36\frac{3}{4}^{\circ}$  E., 207 lks.  
dist., mkd. T5S R42E S29 BT.

A ponderosa pine, 15 ins. diam., bears S.  $6^{\circ}$  W.,  
73 lks. dist., mkd. T5S R42E S30 BT.

A ponderosa pine, 8 ins. diam., bears N.  $34\frac{1}{2}^{\circ}$  W.,  
44 $\frac{1}{2}$  lks. dist., mkd. T5S R42E S19 BT.

Set 5 ft. steel fence post alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, determined at record  
distance from the original bearing trees:

A fir, 22 ins. diam., bears N.  $78^{\circ}$  W., 38 lks.  
dist., with healed blaze. (Record, N.  $88^{\circ}$  W.)

A western larch, 14 ins. diam., bears S.  $13^{\circ}$  E.,  
31 lks. dist., with healed blaze. (Record,  
S.  $5^{\circ}$  E.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 5 S R 42 E  
 $\frac{1}{4}$  S 19  
S 30  
1971

from which new bearing trees

A fir, 16 ins. diam., bears N.  $30\frac{1}{2}^{\circ}$  E., 29 lks.  
dist., mkd.  $\frac{1}{4}$  S19 BT.

A fir, 12 ins. diam., bears S.  $4\frac{1}{2}^{\circ}$  E., 52 lks.  
dist., mkd.  $\frac{1}{4}$  S30 BT.

UNION COUNTY  
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 394-2013R