

V-3 T55 R42E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON POST 28" Long 22" IN Ground
with 5' STEEL FENCE Post Along Side

T55 R42E
 1/4 S30
 S31
 MKD
 1971

ACCESSORIES : DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A PINE 16" BRS. N 41 3/4° W E 6 1/2 LKS. MKD 1/4 S30 BT
 A FIR 9" BRS. S 55° E 65 LKS. MKD 1/4 S31 BT

Work Done By S. ABRIGHT Title CADASTRAL SURVEY Date 9/27/87 State Registration No. RLS 838 or Agency RLM
 Certified Cor. Record Prepared ? Yes No Filed At: _____ Date _____

REMARKS

Index File No. T. R. M. Tract or Surv. No. Cor.

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-28-87

By G. LANGLITZ, DEPUTY

File No. 463-87R

V-3

45
TSS42 V03

T. 5 S., R. 42 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 42 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivision, T. 5 S., R. 42 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by James P. Currin,
Deputy Surveyor, in 1898)

The 1/4 sec. cor. of secs. 30 and 31, monumented with the original stone, 18 x 12 x 3 ins., firmly set, 10 ins. in the ground, with chisel marks visible on N. face, from which the original bearing trees:

A ponderosa pine, 29 ins. diam., bears N. 8° E., 67 lks. dist., with scribe marks S30 visible on opened blaze. (Record, N. 5° E.)

A root hole, bears S. 80° E., 15 lks. dist., with a down ponderosa pine alongside, 40 ins. diam., with scribe marks 1/4 S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 5 S R 42 E
1/4 S 30
1/4 S 31
1971

from which new bearing trees

A ponderosa pine, 16 ins. diam., bears N. 41 1/2° W., 86 1/2 lks. dist., mkd. 1/4 S30 BT.

A fir, 9 ins. diam., bears S. 55° E., 65 lks. dist., mkd. 1/4 S31 BT.

Deposit corner stone and set 5 ft. steel fence post alongside iron post.

The cor. of secs. 19, 20, 29, and 30, determined at record distance from the original bearing trees:

A ponderosa pine, 37 ins. diam., bears N. 86 1/2° E., 85 lks. dist., with illegible scribe marks visible on open blaze. (Record, N. 81° E.)

TSS 42 V03

TSS 42 V03

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By M. S. L. DEPUTY

File No. 395-2022