

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


Index File No. A-17

History of original corner establishment:

A pine post 4"x4"x4", 24" in ground. from which:

- a 12" pine bears N35°E, 48 lks.
- a 12" pine bears S50°E, 48 lks.
- a 6" pine bears S20°W, 28 lks.


Original corner established in 1884 by William B. Barr under contract #492



Description of corner evidence found:
None.

Description of monument and accessories established to perpetuate the original location of this corner: Cap is stamped:

Set 2½"x30" aluminum capped aluminum pipe rising 4" in mound of stones.
Set steel fencepost 3' west of corner.



New BT's
A 7" L. Pine bears S36½°E, 112.2 ft., blazed&scribed CC T6S R35½E S2 BT
A 5" L. Pine bears S20°W 68.4 Ft., blazed&scribed X BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982.

Compass Declination: 19½°E
Witness: J. Sutton
I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on July 16, 1986.



UNION COUNTY SURVEYOR
Date Received <u>8-26-86</u>
Date Filed <u>9-11-86</u>
By <u>G. LANGLITZ DEPUTY</u>
File No. <u>144-86 R</u>

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by (DEPUTY)
(COUNTY OFFICIAL)

SEE SURVEY 27-86