


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. E-19

History of original corner establishment:

A pine post 3'x3"x3" with marked stone 12" in ground with a mound of earth 1 1/2 ft. high, 3 1/2 ft. at base.

pits, 18"x18"x12" east and west of corner, 5 1/2 ft.



Original corner established in 1883 by William B. Barr under contract #492

Description of corner evidence found:
None.

Description of monument and accessories established to perpetuate the original location of this corner: Cap is stamped:

Set 2 1/2"x30" aluminum capped aluminum pipe rising 8". No stones available.
Set steel fencepost 3' east of corner.

T6S R35 1/2 E
1/4 S2
S11
RLS 1848
1986

New BT's:
A 4" W. Fir bears N76 1/2°W, 91.9 ft. blazed & scribed 1/4 S2 BT
A 5" W. Larch bears S56 1/2°E 97.3 ft., blazed & scribed 1/4 S11 BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982.

Compass Declination: 19 1/2°E
Witness: J. Sutton
I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on Aug 15, 1986.



UNION COUNTY SURVEYOR	
Date Received	<u>8-26-86</u>
Date Filed	<u>9-11-86</u>
By	<u>G. LANGRISH, Deputy</u>
File No.	<u>148-86 R</u>

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)