


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. J-23

History of original corner establishment:

Original corner established in 1883 by William B. Barr under contract #492. Set a basalt stone, 12"x10"x5", 8" in the ground. From which: A 4" Pine bears N10°W, 5 lks. A 6" Pine bears S45°W, 10 lks.



Description of corner evidence found:

Found original stone with "1/4" on north face, undisturbed. (record size) BT's found: A 5" dead&down lodgepole pine bears N10°W, 5 lks. open blaze, scribing visible: "1/4S" A 10 1/2" dead and down lodgepole pine bears S45°W, 10 lks. Blaze healed, I did not open.

Description of monument and accessories I established to perpetuate the

original location of this corner: Cap is stamped: At location of original stone, I set a 2 1/2"x30" aluminum capped aluminum pipe rising 12" in a mound of stones. Set steel fencepost 3 1/2 ft. North of corner.

T6S R35 1/2 E 1/4 S 12 S 13

New BT's:

An 8 1/2" D. Fir bears N39°E, 13.2 ft., blazed & scribed: 1/4S12BT A 5 1/2" W. Larch bears S59 1/4°E, 45.5 ft., blazed & scribed: 1/4S13BT

RLS1848 1987

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. A 3/4" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

Corner is on summit of ridge running NW'ly, 650 ft. South of 35" P. Pine with location poster on South side of Rd. 5178, 0.4 mi. SE'ly from its intersection with 5178017.

Compass declination: 20 1/2°E Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on June 30, 1987.



UNION COUNTY SURVEYOR Date Received 8-19-87 Date Filed 8-24-87 By G. LANGLITZ, DEPUTY File No. 72-87 R

Office of..... County of..... State of..... I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19..... by..... (COUNTY OFFICIAL) (DEPUTY)

5-23