## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Н	story of o	origin	al corner est	ablis	hment: (	Origina	al corner	esta	ablished
							Contract		
A	12°x10	)"x8	" stone	was	set	, from	which:		

a 12" Tamarack bears N35°E, 30 lks.,

a 24" Tamarack bears S45°E, 16 lks.,

a 12" Tamarack bears N70°W, 30 lks., and a 12" Tamarack bears S40°W, 12 lks.

Index File No. N-17 DIAGRAM T6S R35 1/2E 15 14 22 23

Description of corner evidence found:

No corner monument found.

Bearing Trees Found:

14" W. Larch, dead & down, bears N35°E, 30 lks., open blaze, scribing visible: T6S R35 1/2E S14.

11.5" W. Larch, dead standing, bears S45°E, 16 lks., partially healed

blaze, scribing visible: E S23. 10" W. Larch stump bears S40°W, 12 lks., base of blaze "T" visible. Cut off portion scribing visible: W/S22.

8" W. Larch, dead & down, bears N70°W, 30 lks., open blaze, blazing faint, unreadable.

Description of monument and accessories I established to perpetuate the Cap is stamped: original location of this corner: Set 2.5"x30" aluminu aluminum capped aluminum pipe T6S R35 1/2E rising 5" above ground. Set steel fence post S15 S14 3 ft. north of corner. S22 S23 New BT's: RLS 1848 10" W. Larch bears N72 1/2°E, 66.8 ft.,
blazed & scribed: T6S R35 1/2E S14 BT. 1986

12" D. Fir bears S16 1/2°E, 49.2 ft.,
blazed & scribed: T6S R35 1/2E S23 BT.

9" D. Fir bears S27 1/4°W, 54.6 ft., blazed & scribed: T6S R35 1/2E S22 BT. 11" D.Fir bears N53 1/2°W, 32.9 ft., blazed & scribed: T6S R35 1/2E S15 BT.

Attached 3/4" brass washer marked RLS 1848 to the lower blazes. blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March 1982.

To find corner, from 5175 take 5175322 northerly 0.6 miles. spur goes southeast up the hill. The corner is northeasterly over the ridgetop from the end of the spur on a northeasterly slope

Compass Declination: 19 1/2°E, Witness: J. Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on March 25, 1986.

REGISTERED **PROFESSIONAL** AND SURVEYOR

> OREGON JULY 13, 1979 B. A. SUTTON 1 8 4 8

> > 37-86

File No

Office of	County of				
for record on the day of	State of, / hereby certify that the within instrument was filed in this office for record on the day of				
(COUNTY OFFICIA	AL) (DEPUTY)	<ul> <li>Волого и постоя проведуем проведуем проведуем проведуем постоя постоя по по постоя по по</li></ul>			
Form R6-7100-57 (9/71)	ு்ப.S. GOVERNMENT PRINTING	Deta Received 5-21-86 DEFICE - 1983-793-276 Date Filed 5-22-86			