


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. V-09

History of original corner establishment:

On the Auxiliary Meridian this Original corner established in 1881 by Eugene P. McCornack under contract #398. He set a stone, 16"x14"x8", 10" in ground. From which:
A 12" Spruce bears N55°E, 22 Lks.
A 30" Spruce bears S75°E, 16 lks.



Description of corner evidence found:

Found original stone, firm in place with top broken, faint grooves on north side.
Found the following original bearing trees:
A 9½" dead & down Spruce bears N55°E, 22 lks., open blaze, full scribing visible.
A 25" Spruce stump, 5' high, bears S75°E, 16 Lks., open blaze, full scribing visible.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the original stone, I set a 2½"x30" aluminum capped aluminum pipe rising 6 in a mound of stones.
Set steel fence post 3' North.

Cap is stamped: T6S R35½E
|S28
|S33
RLS1848
1987

New BT's:

A 7" Spruce bears N35°E, 21.2 ft., blazed&scribed: T6SR35½ES28BT
An 8" Spruce bears S61½°E, 26.4 ft., blazed&scribed: T6SR35½ES33BT

Painted blazes and attached signs as per Standard specifications for Cadastral Surveys, USFS Region 6, March 1982. A ½" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

Corner is just west of Sheep Creek. Leave Sheep Creek Road (Rd. 5182), 0.6 mile NW'ly from 5182120 at the north edge of clear cut, go southwest to corner about 300 ft.

Compass declination: 20°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on June 25, 1987



UNION COUNTY SURVEYOR

Date Received 8-19-87
Date Filed 8-24-87
By G. LANGLITZ DEPUTY
File No. 75-87R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)