


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. C-17

History of original corner establishment:

Original subdivision of T6S, R35E was by Herman D. Gradon under Contract No. 499, approved November 24, 1884. At this corner he set a stone 36x12x10, from which a 7" Mahogany bears N86°E, 9 lks. and a 24" Juniper bears N68°E, 50 lks.



Description of corner evidence found:

No corner monument or evidence found.

UNION COUNTY SURVEYOR
Date Received 10-17-84
Date Filed 10-24-84
By G. LANGLITZ, DEPUTY
File No. 1002-84 R

Description of monument and accessories established to perpetuate the original location of this corner: Corner set by proportion.

Set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 17" above ground in rock mound. Cap is stamped; Set steel fence post with signs 4.0 ft. north of corner.

New BT's:

- 5" P. Pine bears S70°E, 24.5 ft., blazed and scribed; 1/4 S2 BT.
- 7" P. Pine bears S53.5°W, 26.6 ft., blazed and scribed; 1/4 S3 BT.

T6S
1/4
S3 + S2
RLS 1844
1984

Brass LS 1844 disc in lower end of blazes. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found 1300 ft. west of Road 5160-147 and 200 ft. north of large clearing.

I hereby certify the above described corner monument and/or accessories was established as described on September 17, 1984.

REGISTERED PROFESSIONAL LAND SURVEYOR
David E. Scott
OREGON
JULY 13, 1979
DAVID E. SCOTT
1844

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)