


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. C-23

History of original corner establishment:

None.



Description of corner evidence found:

No corner monument or other accessories found.

<b>UNION COUNTY SURVEYOR</b>
Date Received <u>10-17-84</u>
Date Filed <u>10-24-84</u>
By <u>G. LANGLITZ DEPUTY</u>
File No. <u>1005-84R</u>

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2.5" aluminum cap on 2 3/8x30 aluminum pipe rising 14" above ground in mound of dirt and rock.

Set steel fende post 3.0 ft. south of corner.

New BT's:

A 5" Tamarack bears S12°W, 20.9 ft., blazed and scribed C1/4 S1 BT.

A 12" Tamarack bears S17°E, 34.5 ft., blazed and scribed: C1/4 S1 BT.

Brass LS 1844 disc in lower end of blazes. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination; 19 3/4°E

Witness: Duane Scott

Corner is found on west side of hill, 150 ft. east of road. 1320 ft. east of Sheep Creek.

Rd. 5160-092 1/2 mi. north of fence line.

CW 1/16 is 250 ft. east of road on creek bank, thence 1320 ft. east to C1/4.

I hereby certify the above described corner monument and/or accessories was established as described on September 15, 1984.

Cap is stamped:

T6S R35E

C 1/4 • S1

RLS 1844  
1984

REGISTERED PROFESSIONAL LAND SURVEYOR
<i>David E. Scott</i>
OREGON JULY 13, 1979 DAVID E. SCOTT 1844

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)