## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The original subdivision of T6S, R35E, was by Herman D. Gradon under Contract No. 499, approved November 24, 1884. At this corner he set a stone 18x8x6, from which an 11" Pine bears N21°E, a 16" Pine bears S60°W, 7 lks., a 10" Pine bears S49°E, (distance is unreadable), and an 8" Pine bears N54°W, 83 lks.

Index Fi	le No. E-17
DIAGRAM	
T6S	R35E
3 10	2

Description of corner evidence found:

Found stone 13x8x6, firmly set.

Bearing trees found:

A 24" P. Pine stump 18" high, bears S50°E, 84.0 ft., scribed: (BT)

A 16" P. Pine stump bears N54°W, 54.8 ft.

A 22" P. Pine, dead and down, bears N21°E, 52.1 ft.

Description of monument and accessories I established to perpetuate the original location of this corner: Cap is stamped:

T6S R35E

Set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 14" above ground in mound of stone. Buried original stone on north side of cap. Set Steel fence post 4.0 ft. north of corner.

S3 | S2 S10 S11 RLS 1844 1984

New BT's:

5" P. Pine bears N28 3/4°W, 50.0 ft., B&S T6S R35E S3 BT. 14" P. Pine bears S65.5°W, 34.8 ft., B&S T6S R35E S10 BT. 11" P. Pine bears S34.5°E, 29.3 ft., B&S T6S R35E S11 BT. 8" Juniper bears N73 1/4°E, 82.7 ft., B&S T6S R35E S2 BT.

Brass LS 1844 disc in lower end of blazes. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found 300 ft. north of Rd. 5160 on south slope, 800 ft. east of Rd. 5160-157.

I hereby certify the above described corner monument and/or accessories was established as described on August 2, 1984.354.

REGISTERED PROFESSIONAL AND SURVEYOR Vavid &

> OREGON DAVID E. SCOTT 1844

Office of	1844
for record on the day of	office UNION COUNTY
(COUNTY OFFICIAL)	

Form R6-7100-57 (9/71)

Date Received 10-17-84 Date Filed GPO 798-276