CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1881 by Eugene P. McCornack under Contract No. 398.

A post was set, from which: a 36" Tamarack bears N65°E, 34 lks., and a 36" Tamarack bears S30°W, 12 lks. Index File No. C-28 |

DIAGRAM

T6S
R35 1/2E R36E
1/4
S1 S6

UNION COUNTY SURVEYOR

Date Received 6-19-86

Date Filed 6-19-86

Description of corner evidence found:
No corner monument found.

Bearing trees found:

24" W. Larch stump bears S30°W, 12 lks with matching butt cut with open blazes scribed: 1/4 S BT, lying 5 ft. west.
20" W. Larch, dead & down, bears N65°E, 34 lks., open blaze,

scribing faint.

Description of monument and accessories I established to perpetuate the Cap is stamped: original location of this corner:

Set 2.5"x30" aluminum capped aluminum pipe rising 6" above ground. No stones available. Set steel fence post 3 ft. north of corner.

R35 1/2E R36E 1/4 S1 S6 RLS 1848

T6S

1986

New BT's:

12" W. Larch bears N39 3/4°E, 60.8 ft., blazed & scribed 1/4 S6 BT.

12.5" D. Fir bears S89°W, 8.1 ft., blazed & scribed 1/4 S1 BT.

Attached 3/4" brass washer marked LS 1848 to blazes. Painted blazes and attached signs as per <u>Standard Specifications</u> for <u>Cadastral Surveys</u>, USFS Region 6, March 1982.

To find corner: at 1.3 milepost on 5125, take river crossing south--left fork at foot of hill in draw just beyond green gate. Follow road 1/2 mile southeasterly--take right fork and follow road up the draw about 1 mile (road hooks around head of draw). Corner is 200 ft. before switchback in middle of draw 150 ft. west of road.

Compass Declination: 19 1/2°E Witness: J. Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on June 11, 1986

PROFESSIONAL LAND SURVEYOR	1
Bullar	
OREGON JULY 13, 1979 B. A. SUTTON 1 8 4 8	

Office of	County of
State of I hereby cer	tify that the within instrument was filed in this office
for record on the day of	, 19
(COUNTY OFFICIAL)	by(DEPUTY)