CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. J-03

History of original corner establishment:

Original corner established in 1883 by William B. Barr under contract #492. Set a pine post, 3"x3"x3' 24" in the ground. From which:

An 8" Pine bears N, 6 lks. An 8" Pine bears S10°W, 18 lks. T6S R36E

Description of corner evidence found:

Found discoloration of soil and badly decayed remains of original post down to a foot below surface. BT's found:

- A 13" dead and down lodgepole pine bears S20°W (Orig. S10°W), 18 lks. blaze healed on underside.
- A 12" dead and down lodgepole pine; stump bears North 6 lks. from corner. I opened blaze. "BT" visible.

Description of monument and accessories lestablished to perpetuate the original location of this corner:

At location of remains of original post, I set a 2½"x30" aluminum capped aluminum pipe rising 5" in a mound of stones and earth. Set steel fencepost 3 ft. North

New BT's:

T6S R36E

T6S R36E

T6S R36E

A 6" W. Larch bears N544°W, 18.8 ft., blazed & scribed: \\\\\delta S7BT

A 4½" Western Larch bears S58¾°W, 73.9 ft., blazed & scribed: ¼S18BT

Painted blazes and attached signs as per <u>Standard Specifications</u> for <u>Cadastral Surveys</u>, <u>USFS</u> Region 6, March 1982. A 3/4" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

Corner is approx. 65 ft. north of pond. Walk 21 chains west from a 10" white fir with location poster on east side of Rd. 5178085, 0.4 mi. south from 5178080.

Compass declination: 21°E Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on June 25, 1987.



UNION COUNTY
SURVEYOR

1987

Date Received 8-19-87

Date Filed 8-24-87

By G. LANGE ITZ DEPUTY

File No. 89 -87 R