Index File No. J-13

## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner es	stablished in 1883	DIAGRAM
by William B. Barr under Contract No. 492.		T6S R36E
A pine post was set, from which: a 12" Pine bears N20°E, 37 lks., an 8" Pine bears S50°E, 80 lks., a 10" Pine bears S50°W, 24 lks.,	and	9   10   16   15
an 8" Pine bears N55°W, 22 lks.		
	UNION COUNTY SURVEYOR	
	Date Received 6-19-86	
	Date Filed 6-19-86	
Description of corner evidence found:	BY G. LANGLITZ DOPUTY	
No corner monument found.	File No. 93-86 R	
Bearing trees found:  Decayed remains of L. Pine, diames scribing visible: BT.  An 8" L. Pine, dead & down, bear visible: T6S R36E S15 BT.  A 10" L. Pine, dead & down, bear scribing visible: T6S R36E.	s S50°E, 80 lks, op	en blaze, scribing
Description of monument and accessories I established original location of this corner:  Set 2.5"x30" aluminum capped alumi:		is stamped: T6S R36E
rising 4" above ground. (No stones Set steel fence post 3 ft. north o	available.)	<u>s 9   s10   s16   s15   </u>
New BT's:		RLS 1848
14" D. Fir bears N51°E, 12.8 ft. blazed & scribed: T6S R36E S10 8.5" W. Larch bears S59°E, 34.6 12.5" W. Larch bears S48°W, 57.5 14.5" W. Larch bears N65 1/2°W, T6S R36E S9 BT.	BT. ft., blazed & scrib ft., blazed & scri	bed: T6S R36E S16 BT
Attached 3/4" brass washer marked and attached signs as per Standard USFS Region 6, March 1982.		
Compass Declination: 19 1/2°E Witness: J. Sutton		
I hereby certify that the above de corner monument and/or accessories perpetuated as hereon described on	was	REGISTERED PROFESSIONAL LAND SURVEYOR OREGON JULY 13, 1979 B. A. SUTTON
Office of		
Office of		
for record on the day of		
(COUNTY OFFICIAL)	(DEPUTY)	