

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


N-1

Index File No. N-25

History of original corner establishment:

Original corner established by Eugene P. McCornack in 1881 under Contract No. 398.

An 18"x12"x10" stone was set, from which:  
an 8" Pine bears N30°E, 40 lks.,  
a 6" Pine bears S35°E, 5 lks.,  
a 10" Fir bears S35°W, 75 lks., and  
a 24" Tamarack bears N48°W, 40 lks.



Description of corner evidence found:

Found 18x12x10 stone, marks visible, lying on top of the ground S40°W 4 ft. from the corner position. At the corner position I found an indentation in the ground the size of the stone, filled with organic material. Indentation fits the S19 & S24 BT's.

Bearing trees found:

10" L. Pine, dead & down, bears S35°E, 5 lks, open blaze, scribing visible: T6S R36E S19 BT.  
14.5" Live Douglas Fir bears S35°W, 75 lks., blaze healed.  
14.5" W. Larch, dead & leaning, bears N28 1/2°W, 24.1 ft., open blaze, scribing visible: T6S R35 1/2E S13 BT.

\*Note: The call in the original of N48°W, 40 lks. appears to be in error for the bearing tree in S13.

Description of monument and accessories I established to perpetuate the original location of this corner:

Cap is stamped: T6S  
R35 1/2E R36E  
S13 | S18  
S24 | S19  
RLS 1848  
1986

Set 2.5"x30" aluminum capped aluminum pipe rising 4" above ground. Set steel fence post with 54-9 sign 3 ft. north of corner.

New BT's:

8.5" W. Larch bears N52°E, 30.7 ft., blazed and scribed: T6S R36E S18 BT.  
7.5" D. Fir bears S69°E, 17.6 ft., blazed & Scribed: T6S R36E S19 BT  
7.5" W. Fir bears N77 1/2°W, 19.9 ft., blazed & scribed: T6S R35 1/2E S13BT

Attached 3/4" brass washer marked RLS 1848 to the lower blazes. Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March 1982.

To find corner, follow 5178 from 5178029 southeasterly 0.35 mi. to location poster on 5" fir on left. Corner is north 330 ft. in dense tangled thicket on a gentle westerly slope.

Compass Declination: 19 1/2°E

Witness: J. Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on May 17, 1986.



Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received 5-21-86  
Date Filed 5-22-86  
By G. LANGLITZ DEPUTY  
File No. 35-86 R