## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established in 1881 by Eugene P. McCornack under contract #398. Set a basalt stone, 30"x20"x8', 20" in ground. From which:

A 24" Fir bears N50°E, 120 Lks. A 12" Fir bears S45°E, 125 lks. A 24" Fir bears S40°W, 80 lks. A 12" Pine bears N20°W, 130 lks. Index File No. V-25

## DIAGRAM

T6S R35≒E R36E S25 | S30 S36 S31

## Description of corner evidence found:

Found broken stone, no marks at corner location.

Found the following original bearing trees:

A 27" Doug Fir (live, poor condition), bears N50°E, 120 Lks., blaze healed over from the left side.

A 15½" Fir, dead & down bears S40°W, 80 Lks., open blaze on under side, full scribing visible.

A 142" dead standing Ponderosa Pine bears N20°W, 130 Lks., opened blaze, 35 E visible.

Found no trace of the Section 31 bearing tree.

## Description of monument and accessories I established to perpetuate the original location of this corner:

Cap is stamped: At the position established from the orig. BT's, I R355E R36E set a 25"X30" aluminum capped aluminum pipe rising S25 | S30 S36 | S31 24" in a mound of stones. Set steel fencepost 1.2' North in mound of stones. RLS1848 New BT's:

1987 An 8" D. Fir bears N71%°E, 8.4 ft., blazed&scribed T6SR36ES30BT A 7" D. Fir bears S71°E, 36.2 ft., blazed&scribed T6SR36ES31BT A 13½" P. Pine bears S24¾°W, 86.7 ft., blazed&scribed: T6SR35½ES36BT An 8" D. Fir bears N69¼°W, 65.1 ft., blazed&scribed: T6SR35½ES25BT

Painted blazes and attached signs as per Standard specifications for Cadastral Surveys, USFS Region 6, March 1982. A 3" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

From Rd. 5185050 follow summit of ridge 3 mile easterly&northerly to point of ridge where it breaks steeply to the North. Go west 2000 ft., corner is West of sparse mahogany, partially open hillside at the head of two draws, one to the NW, and one to the SW, on a WNW'ly sloping ridgetop. REGISTERED PROFESSIONAL AND SURVEYOR

Compass declination: 20%°E Witness: Jeremy Sutton

I hereby certify that the above desc acce here C

COUNTY OFFICIAL

., .	
cribed corner monument and/or	OREGON
essories were established as	JULY 13, 1979
eon described on June 29, 1987.	B. A. SUTTON
Office of	1848
Office of	
State of, I hereby certify that the within for record on the day of	instrument was filed in this office
19 19	

..... by ......

UN	ION	COUNT	-
	SURV	/eyor	

Date Received 8-19-87 Date Filed ANGLITZ File No. 76-87 R

Form R6-7100-57 (9/71)

\$U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276

Too

(DEPUTY)