


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. V-17

History of original corner establishment:

Original corner established in 1883 by William B. Barr under contract #492. Set a granite stone 20"x18"x12", 15" in ground. From which:
Raised a mound of stones in Section 26.
An 8" Pine bears S40°E, 25 lks.
An 8" Pine bears S35°W, 50 lks.
A 12" Tamarack bears N40°W, 112 lks.



Description of corner evidence found:

Found original stone, broken, no notches (together the pieces measure 18"x16"x11"). Largest piece was firm in place and good position with the original bearing trees.
Found the following original accessory and bearing trees:
Found strewn stones NE of original stone 3-6 ft. diameter 4 feet from corner.
A decayed Pine and root hole (R36E visible) bears S40°E, 25 lks.
A decayed Pine and root hole full scribing visible, bears S35°W, 50 lks.
A 24½" Western Larch (live, good condition) bears N40°W, 112 lks., blaze healed over, did not open.

Description of monument and accessories established to perpetuate the original location of this corner:

At the position of the original stone, I set a 2½"x30" aluminum capped aluminum pipe rising 7" in a mound of stones and placed orig. stone on North side in mound. I set a steel fence post 3' North of corner

Cap is stamped:
T6S R36E
S27 | S26
S34 | S35
RLS1848
1987

New BT's:

- A 9" Western Larch bears N39½°E, 101.4 ft., blazed&scribed: T6SR36ES26BT
- A 15½" Western Larch bears S39½°E, 43.0 ft., blazed&scribed: T6SR36ES35BT
- A 10½" Western Larch bears S58½°W, 76.1 ft. blazed&scribed; T6SR36ES34BT

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. A ¾" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

From Rd. 5125 follow 5138 Southerly and Easterly 3 miles to where it crosses a creek (flows NW). Go West 300 ft. to Grande Ronde River. Follow South upstream ¼ Mile to a 10" Spruce with red band and yellow tag on West bank. Corner is West, 250 ft. on Easterly slope.

Compass declination: 20½°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on June 29, 1987.

REGISTERED PROFESSIONAL LAND SURVEYOR

Jeremy Sutton
OREGON
JULY 13, 1979
B. A. SUTTON
1848

UNION COUNTY SURVEYOR

Date Received 8-19-87

Date Filed 8-24-87

By G. LANGLITZ, DEPUTY

File No. 95-87 R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)