


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. C-1

History of original corner establishment:

Corner was originally established by W. B. Barr, under G.L.O. contract No. 388, in September, 1881. Surveyors General's notes state: "Set stake 4 ft. long 4 in. diam. 18 in. in ground for 1/4 sec. corner from which Fir 5 in. diam. bears S19°W, 16 lks. dist. Fir 6 in. diam. bears N32°E, 21 lks. dist."




Description of corner evidence found:

Found stump 24" in diam. with scribed T left. Measured N19°E, 10.5 ft. A stump (rotten) bears N36°E, 18.5 ft. No trace of scribing. 54-3 on stump.

Description of monument and accessories established to perpetuate the original location of this corner:

At center of above described point set 2 1/2" x 30" galvanized pipe and brass cap marked: Set pipe 24" in the ground and placed small mound of stone around. From which, by magnetic declination of N20°E: A 9" fir bears N84°E, 17.2 ft. scribed 1/4 S6 BT. A 9" pine bears S41°W, 53.6 ft. scribed T6SR37E BT. Placed 54-3s and brass washers stamped PLS 1051 on BTs. Painted blazes red and 6" red band around. Placed 54-4 on steel fence post 5' South of corner. Placed 54-5 on small fir 15' East of corner.



I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers
Robert S. Stevens

July 18, 1979

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of.....County Surveyor..... County of.....Union.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 6th day of.....December.....1979

.....*J. V. [Signature]*..... by*D. L. Landers*.....
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received _____

Date Filed _____

By _____

File No. 755-84R