


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

Index File No. C-9

**History of original corner establishment:**

Corner was originally established by W.B. Barr, under G.L.O. contract No 338 in September, 1881. Surveyor General's notes state: "Set post 4 ft. long, 4 ins. square, 18 ins. in the ground for 1/4 section corner marked 1/4S on W. face. From which: A pine 40 ins. diam. bears S15°E, 20 lks. dist marked 1/4S BT. A pine 40 ins. diam. bears S60°W, 22 lks. dist marked 1/4S BT."




**Description of corner evidence found:**

Found no trace of corner post or BTs.

**Description of monument and accessories established to perpetuate the original location of this corner:**

Set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 24" in the ground and mound of stone around to cap. From which by magnetic declination of N20°E: A 9" Fir bears N89°E, 28.8 ft. scribed 1/4S4 BT. A 15" Tamarac bears N37°W, 27.8 ft. scribed 1/4S5 BT. Painted blazes red and 6" red band around. Placed CZ loc. tags, BT tags and property tags. Placed location tag on 8" Pine 4' West. Placed 54-4 on steel fence post 5' South of the corner.



I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel T. Rowland  
Ribert Boling

June 10, 1980

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Barry B. Barbour*

OREGON  
OCT. 17, 1975  
BARRY B. BARBOUR  
1051

Office of..... County Surveyor..... County of..... Union.....  
State of..... Oregon..... I hereby certify that the within instrument was filed in this office  
for record on the 3<sup>rd</sup> day of July....., 1980  
..... by .....

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY  
SURVEYOR**

Date Received                     

Date Filed                     

By                     

File No. 762-84R