


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. E-3

History of original corner establishment:

Corner was originally established by W. B. Barr, under G. L. O. contract No. 388, in September, 1881. Surveyors General's notes state: "Set marked basalt rock 12 X 10 X 6 for 1/4 Sec. corner, from which a pine 36 ins. diam. bears S5°E, 86 lks. dist. A pine 50 ins. diam. bears N70°W, 42 lks. dist."



Description of corner evidence found:

Found small mound of stone and painted rock about record size. No Markings could be found. Found a pine stump bearing S09°E, 51.1 ft. scribed "7 BT". A 39" pine stump bears N60°W, 30.6 ft., scribed "BT" on part of grown over blaze. 54-3s on old BT stumps.

Description of monument and accessories established to perpetuate the original location of this corner

At center of the above described stone, set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 24" in the ground and mound of stone around to cap. From which: by magnetic declination of N20°E: A 15" fir bears S12°E, 32.5 ft. scribed 1/4S7 BT. A 9" pine bears N54°E, 36.3 ft. scribed 1/4S6 BT. Painted blazes red and 6" red band around. Placed 54-3s and brass washer stamped PLS 1051 on BTs. Old location tags on new SE BT, on a tree 35' north and 1978 tag on tree at road about 265' east. Placed 54-4 on a steel fence post 5' East of corner.

T6SR38E
S6
1/4 —+
S7
OR PLS 1051
1979

REGISTERED PROFESSIONAL LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1875
BARRY B. BARBOUR
1051

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers
Robert S. Stevens

July 18, 1979

Office of County Surveyor..... County of Union
 State of Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the 6th day of December, 1979
J. Paul (COUNTY OFFICIAL) by *J. Sepler* (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____

Date Filed ^{GRO 796-333} _____

By _____

File No. 767-84R