
## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File NO. F.-9

## History of original corner establishment:

Corner was originally established by W.B. Barr, under G. L. O. contract No. 338 in September, 1881. Surveyor General's notes state: "Set basalt stone 14 X 10 X 8 ins. in the ground for corner sections 4, 5,8, and 9. Marked 5 notches S. and 4 notches E edges. Frome which: A pine 8" in diameter bears S69°W, 50 lks. dist. marked T6SR38ES8 BT. A pine 15" in diameter bears N81°W, 60 lks. dist. marked T6SR38ES5 BT. A pine 36" in diameter bears N35°WE, 7 lks. dist marked T6SR38ES4 BT. A fir 18" in diameter bears S55°E, 20 lks. dist. marked T6SR38ES9 BT."



T6S R38E

OR PLS 1051

1980

File No. 771-84R

S5

S8

## Description of corner evidence found:

Found 14" X 9" X 8" basalt stone set in E-W fence clearly marked with 4 notches on south edges. From a 40" pine stump bears N47°E, 4.5 ft. scribed "BT". No other BTs found.

## Description of monument and accessories I established to perpetuate the original location of this corner:

Set pipe 25" in the ground and mound of stone around to cap. Placed marked stone at base of pipe.

From which by magnetic declination of N20°E:

A 12" tamarac bears N16°E, 51.3 ft. scribed T6SR38ES4 BT.

A 14" tamarac bears S31°E, 91.8 ft. scribed T6SR38ES9 BT.

A 14" pine bears S15°W, 117.2 ft. scribed T6SR38ES8 BT. A 15" fir bears N18°W, 38.5 ft. scribed T6SR38ES5 BT. Placed C.Z. loc. tags and brass washers on BTs. Placed 54-4 on steel fence post 5' North of the corner.

REGISTERED PROFESSIONAL LAND SURVEYOR OREGON OCT. 17, 1875 BARBOUR 1051

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel T. Rowland Robert Boling

May 20, 1980

for record on the. 3. day of	t the within instrument was filed in	n this office
for record on the		UNION COUNTY
(COUNTY OFFICIAL)	(DEPUTY)	
Form R6-7100-57 (9/71)		Date Received
		Date Filed