


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Not Set.

Index File No. G-4



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" X 30" galvanized pipe and brass cap marked:

Set pipe 25" in the ground and mound of stone around to cap.

From which by magnetic declination of N20°E:

A 6" Fir, bears N37°E, 26.7 ft. scribed CE 1/16 S7 BT.

A 9" Fir, bears N31°W, 38.7 ft. scribed CE 1/16 S7 BT.

Painted blazes red and 6" red band around. Placed 54-3s and brass washers stamped PLS 1051 on the BTs. Placed 54-9 and Crown Zellerbach property sign on a steel fence post 5' north of the corner.

T6S R38E
E 1/16
C — C
S7
OR PLS 1051
1981

I hereby certify that the above corner monument was established as herein described.

Witnesses: Daniel Rowland
Douglas Moser
Beverly Weaselhead

May 12, 1981

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of.....County Surveyor..... County of..... Union
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 26 day of.....June....., 1981.
HOWARD L. PERRY..... by Harry J. Langlit
(COUNTY OFFICIAL)..... (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received _____

Date Filed GPO-798-276 _____

By _____

File No. 782-84R