

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. G-5

History of original corner establishment:

Corner was originally established by W. B. Barr, under G. L. O. contract No. 388, in September, 1881. Surveyors General's notes state; "Marked basalt rock 14 X 12 X 8 for 1/4 sec. corner, from which a Pine 20 in. diam. brs. S85°W, 90 lks. dist. A pine 20 ins. diam. brs. S67°E, 42 lks. dist."



Description of corner evidence found:

Found no trace of corner stone. Found BLM tag and steel fence post, from which a stump with some scribing bears S69°E, 28.0 ft., and a short stump painted BT bears S85°W, 59.1 ft.

Description of monument and accessories established to perpetuate the original location of this corner:

At center of above described point set 2 1/2" X 30" galvanized pipe and brass cap marked:
Set pipe 24" in the ground and mound of stone around to cap.

T6SR38E
1/4
S7 † S8
OR PLS 1051
1979

From which: by magnetic declination of N20°E:
A 12" pine bears N66°E, 52.2 ft. scribed 1/4S8 BT. A 14" pine bears N78°W, 83.9 ft. scribed 1/4S7 BT. Painted blazes red and 6" red band around. Placed 54-3s and brass washer stamped PLS 1051 on BTs. Location tag on tree 20' North. Placed 54-4 on steel fence post 5' South of corner.

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers
Robert S. Stevens

July 20, 1979

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of..... County Surveyor..... County of..... Union
State of..... Oregon..... I hereby certify that the within instrument was filed in this office
for record on the... 6th day of December..... 19... 79
..... by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

UNION COUNTY
SURVEYOR

Date Received ★ GPO-798-276

Date Filed _____

By _____

File No. 783-84R