

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:


Corner established by W. B. Barr under GLO contract no. 388 dated May 7, 1881.

Surveyor General records state:

Set stake 4 ft long 4 ins diam 18 ins in ground for 1/4 sec cor, from which:

- A pine 60 in diam bears N 60° W, 44 lks dist.
- A cottonwood 8 in diam bears S 56° E, 67 lks dist.

G-9



Description of corner evidence found:

Found an old burnt out stump 60 ins in diam. and a mound of stones which bear S 50° E, 25 feet from stump. This is the only stump or tree of proper size in the area, and is accepted as the Section 8 bearing tree.


Description of monument and accessories established to perpetuate the original location of this corner:

Set a 2½ inch brass cap on a 1 inch iron pipe 31 inches long and projecting 5 inches out of the ground with a surrounding rock mound.

Brass cap marked thus:

T 6	S R	38 E
	$\frac{1}{4}$	
S 8		S 9
LS		3-30
1206		1981

I hereby certify that the above corner monument was properly established on March 30, 1981, under my supervision and witnessed by Brad Gordon, Tom Fisk and Jim DeMastus.



Office of County Surveyor County of Union
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 22 day of May, 1981.
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received _____	<small>☆ GPO-798-276</small>
Date Filed _____	
By _____	
File No. <u>785-84R</u>	