## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. J-11

## History of original corner establishment:

Corner was originally established by W. B. Barr, under G. L. O. contract No. 388, in September, 1881. Surveyors General's notes state: "Marked basalt rock 14 X 12 X 4 for 1/4 Sec. corner, from which a Pine 28 in. diam. bears N83 1/2°W, 232 lks. dist. a Pine 24 in. diam. bears S20°E, 186 lks. dist."

T6SR38E
S9
1/4
S16

## Description of corner evidence found:

Found 11 X 10 X 6 inch stone in mound of stone, near a fence corner, clearly marked 1/4 on north face. From which a low cut stump bears N83°W, 153 ft. Stump is 33" in diameter and cut too low to save the scribing. A 24" pine stump bears S22°E, 95 ft. with no visible scribing. (146 links-record 186 links)

## Description of monument and accessories I established to perpetuate the original location of this corner:

At center of the above described stone set 2 1/2"

X 30" galvanized pipe and brass cap marked:

Set pipe 8" in the ground to bedrock and place
mound of stone around to cap. Later a fence
corner and large rock jack were built around the
corner.

T6SR38E

S9

1/4

COR PLS 1051

1979

From which: by magnetic declination of N20°E:
An ll" pine bears N47°W, 63.5 ft. scribed 1/4S9 BT. An ll" pine bears S65°W, 37.2 ft. scribed 1/4S16 BT. Painted blazes red and 6" red band around. Placed 54-3s and brass washer stamped PLS 1051 on BTs. Placed 54-5 on SW BT. Placed 54-4 on steel fence post 5' East of corner.

REGISTERED described.

Witnesses: David L. Landers Robert S. Stevens

July 18, 1979

PROFESSIONAL
LAND SURVEYOR

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1 0 5 1

	County Surveyor Oregon I hereby certify to		this office	
for record	county of December		UNION COUNTY	
7	(COUNTY OFFICIAL)	(DEPUTY)	SURVEYOR	

Form R6-7100-57 (9/71)

Date Received OPO 798,278

Date Filed

By

File No. 793-84 R