## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by W. B. Barr under GLO contract No. 388 dated May 7, 1881. Record states:

Marked basalt rock 14"x12"x8" from which; Pine 30" dia. bears S. 59%° E., 88 lks. Pine 14" dia. bears N. 12%° W., 235 lks.

DIAGRAM T6S R38E 1/4 S16 S15 ORLS 1206 1981

Description of corner evidence found:

In 1981, found 36" dia. partially burnt stump bears N. 121/2° W., 235 lks.

dist. mkd. with BT on partially healed blaze.

Found stump remains bear S. 59½° E., 88 lks. dist., no scribe visible.

Also found original marked 1/4 stone 13"x11"x7" in fence rockjack.

Description of monument and accessories I established to perpetuate the original location of this corner:

In 1981, at the corner point as re-established from the two original found bearing trees, set 1"x30" long galvanized pipe 20" into the ground with 2½" dia. brass cap marked as shown in the corner diagram. Buried the original marked stone 1 ft. north. From which:

A 12" dia. Ponderosa Pine bears N. 70½° W., 42.9 ft. dist. mkd.

1/4 S16 BT.

A 14" dia. Ponderosa Pine bears N. 23° E., 34.0 ft. dist. mkd. 1/4 S15 BT.

Bearing trees added August 24, 1990:

A 14" dia. Ponderosa Pine bears S. 67° W., 63.2 ft. dist. mkd.

1/4 S16 BT.

A 14" dia. Ponderosa Pine bears S. 28° E., 123.6 ft. dist. mkd. 1/4 S15 BT.

The monument is located 8 ft, westerly from a fence intersection.

I hereby certify that the above corner monument was properly re-establishe on October 16, 1981, under my direct supervision and witnessed by Brad Gordon, Tom Fisk, and Jim DeMastus. And also that two additional bearing trees were taken on August 24, 1990, as witnessed by Larry McBroom and Andy Marlette.

	eby certify that the within instrument was filed	
for record on the day of, 19		UNION COUNTY SURVEYOR
Form R6-7100-57 (9/71)	PROFESSIONAL LAND SURVEYOR	Date Received 9-28-90
	OREGON JAMES D. HANLEY 1206	Date Filed 10/1/90  By My place