

Dependent Resurvey of the South Boundary  
(First Standard Parallel South),  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

<p>CHAINS</p> <p>39.770</p>	<p>A ponderosa pine, 16 ins. diam., bears N. 2° W., 25 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base, the corner stone alongside, and set a 6 ft. steel fence post alongside the stainless steel post.</p> <hr/> <p>S. 89° 55' 30" W., beginning new measurement.</p> <p>Descend steep SW. slope, over numerous slate rock outcrops and cliffs.</p> <p>The standard cor. of secs. 31 and 32, determined at record distance from the remains of the original bearing trees:</p> <p>A sawed, rotting fir stump, 15 ins. diam., bears N. 56° E., 184 lks. dist., no marks. (Record, N. 53° E.)</p> <p>A hollow, burned pine stump, 30 ins. diam., bears West, 40 lks. dist., with burned pine log alongside, with axe marks on weathered blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <table border="1" data-bbox="807 1042 1032 1159"> <tr><td></td><td>SC</td><td></td></tr> <tr><td>T 5 S</td><td> </td><td>R 41 E</td></tr> <tr><td>S 31</td><td> </td><td>S 32</td></tr> <tr><td colspan="3">1991</td></tr> </table> <p>from which new bearing trees</p> <p>The S½ of a twin ponderosa pine, 20 ins. diam., bears N. 7½° E., 98 lks. dist., mkd. T5S R41E S32 SC BT.</p> <p>A ponderosa pine, 18 ins. diam., bears N. 76¼° W., 72 lks. dist., mkd. T5S R41E S31 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr/> <p>S. 89° 52' 00" W., on the S. bdy. of sec. 31.</p> <p>Along N. slope, through logged area.</p>		SC		T 5 S		R 41 E	S 31		S 32	1991		
	SC												
T 5 S		R 41 E											
S 31		S 32											
1991													
<p>12.485</p>	<p>From this point, the original closing cor. of secs. 5 and 6, T. 6 S., R. 41 E., bears South, 0.068 chs. dist., determined at record bearing and distance from the remains of the original bearing trees:</p> <p>A root hole, bears N. 33° E., 43 lks. dist., with a piece of fir log alongside with scribe marks T5S E legible.</p> <p>A sawed fir stump, 28 ins. diam., bears S. 70° E., 45 lks. dist., with scribe marks BT on open blaze.</p>												

UNION COUNTY  
SURVEYOR

---

Date Received 3/5/13

Date Filed 3/5/13

By NA Gllm

File No. 104-2013R

Dependent Resurvey of the South Boundary  
 (First Standard Parallel South),  
 T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <p>S 31</p> <hr style="width: 50px; margin: auto;"/> <p>S 6 S 5</p> <p>T 6 S R 41 E</p> <p>CC</p> <p>1991</p> </div> <p>from which new bearing trees</p> <p>A lodgepole pine, 12 ins. diam., bears S. 29½° E., 222 lks. dist., mkd. T6S R41E S5 CC BT.</p> <p>A lodgepole pine, 12 ins. diam., bears S. 27¼° W., 147 lks. dist., mkd. T6S R41E S6 CC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.</p>
14.00	Ascend NE. slope.
26.00	Spur, slopes NW.; desc. W. slope.
40.175	<p>The standard ¼ sec. cor. of sec. 31, determined at the center of an ancient stone mound with the original slate stone, 15 x 12 x 3 ins. (record, 12 x 12 x 3 ins.), loose alongside, mkd. ¼ on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>T 5 S R 41 E</p> <p>¼ S 31</p> <hr style="width: 50px; margin: auto;"/> <p>1991</p> </div> <p>from which new bearing trees</p> <p>A ponderosa pine, 10 ins. diam., bears N. 77° E., 27 lks. dist., mkd. ¼ S31 SC BT.</p> <p>A ponderosa pine, 15 ins. diam., bears N. 50° W., 103 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p>
	S. 89° 28' 00" W., beginning new measurement.
3.15	<p>Descend SW. slope.</p> <p>Track road, 15 lks. wide, bears N. and S., and ravine, drains S.; asc. SE. slope.</p>

<b>UNION COUNTY SURVEYOR</b>	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>McOllin</i>
File No.	184-2013R