


A 9 LAND CORNER RECORD
(Rectangular)

1. T. 65 R. 41E No. A-9 Cor. BEC Mer. W 1/4 State DC N. F. W 1/4 Dist. UNION

2. Corner Status



3. Original Description _____ Vol. _____ Page _____ Where Recorded _____

4. Description of Corners:

5. Investigation Notes:

16" W.L. WITH SCRIBING. DEPARTMENT OF INTERIOR METAL TAG. 8/3/56 BY LA NC

7. Photo Identification

Photo No. ENN-9-45
Ident. By: PIN PUNCHED

8. Plane Coordinate Position Data

State _____ Zone _____

X _____

Y _____

Estab. By _____

Field Book No. _____

Where Filed _____

9. Evaluation

Authentic _____

Needs Verif. _____ Monument _____

Re-estab. _____ Survey _____

Land Status _____

6. Signed E.A. Holbrook Title _____ Date 10/28/66

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-23-87

By G. LANGLITZ, DEPUTY

File No. 377-87R


A-9

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

12.38 From this point, the original closing cor. of secs. 4 and 5, T6S R41E, and bears South, 0.109 chs. dist., determined at record bearing and distance from the remains of an original bearing tree:



A larch snag, 17 ins. diam., bears S.9°W., 28 lks. dist. with fragmentary scribe marks visible on open blaze.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap, from which:

- A larch, 14 ins. diam., bears S.41°E., 133 lks. dist. mkd. T6S R41E S4 CC BT.
- A lodgepole pine, 12 ins. diam., bears S.67°W., 74 lks. dist. mkd. T6S R41E S5 CC BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel post alongside of the stainless steel post.

Description of corner evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, 6" above the ground, with no stones, from which:

- A larch, 16" diam., bears S.41°45'E., 85.89', with a 26" x 3" blaze scribed "T6S R41E S4 CC BT".
- A pine, 14" diam., bears S.67°30'W., 49.26', with a 25" x 4" blaze, (not legible).

Description of monument and accessories I established to perpetuate the original location of this corner:

- A fir, 13" diam., bears N.38°44'W., 22.40', with a 5" x 4" blaze, scribed "BT".
- A pine, 12" diam., bears N.53°42'E., 42.12', with a 11" x 4" blaze, scribed "X BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
 WITNESS TO MONUMENT: DAVID SUTHERLAND
 BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
 BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY
SURVEYOR

Date Received 10/28/98

Date Filed 10/31/98

By R. ROBINSON, Deputy

File No. 116-198R

REGISTERED
PROFESSIONAL
LAND SURVEYOR


M.A. Stoll 9/98

OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a USFS 3 1/4" aluminum capped monument, cap marked per diagram, 22" in the ground, with a mound of stone to cap, from which:

Existing Accessories:

- A pine, 14" in diam., bears S.60°20'W., 15.9', with partial visible scribing
- A fir, 13" in diam., bears N.55°00'W., 17.6', with partial visible scribing
- A larch, 16" in diam., bears S.37°40'E., 93.3', with partial visible scribing

New Accessory:

A fir, 15" in diam., bears N.51°20'E., 48.5', scribed "XBT"

A 3" BLM brass capped pipe, marked CC, 6 " above the ground bears S 00°15'48" W, 6.98'.

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: ERIC GREEN
BEARINGS AND DISTANCES TAKEN TO THE CENTER OF CAP.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY SURVEYOR

Date Received 10/28/98

Date Filed 10/31/98

By R. ROBINSON, DEPUTY

File No. 179-1998R

REGISTERED PROFESSIONAL LAND SURVEYOR

Ronald E. Stoll 9/98

OREGON
JULY 15, 1993
RONALD E. STOLL
2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

Dependent Resurvey of the South Boundary
(First Standard Parallel South),
T. 5 S., R. 41 E., Willamette Meridian, Oregon

12.380

From this point, the original closing cor. of secs. 4 and 5, T. 6 S., R. 41 E., bears South, 0.109 chs. dist., determined at record bearing and distance from the remains of an original bearing tree:

A larch snag, 17 ins. diam., bears S. 9° W., 28 lks. dist., with fragmentary scribe marks visible on opened blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 5 S R 41 E
S 32
S 5 S 4
T 6 S R 41 E
CC
1991

from which new bearing trees

A larch, 14 ins. diam., bears S. 41° E., 133 lks. dist., mkd. T6S R41E S4 CC BT.

A lodgepole pine, 12 ins. diam., bears S. 67° W., 74 lks. dist., mkd. T6S R41E S5 CC BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.

15.00

Top of ascent, over nearly level land.

34.00

Ascend E. slope.

38.85

Rocky spur, slopes SE.

40.030

The standard ¼ sec. cor. of sec. 32, monumented with the original slate stone, 16 x 15 x 5 ins., loosely set 3 ins. in the ground, mkd. ¼ on the N. face, from which the remains of the original bearing tree:

A root hole, bears N. 40° E., 15 lks. dist., with rotten remains of a large pine log alongside, no marks.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
T 5 S R 41 E
¼ S 32
1991

from which new bearing trees

A ponderosa pine, 19 ins. diam., bears N. 33½° E., 21 lks. dist., mkd. ¼ S32 SC BT.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

RL G...

File No.

185-2013R