


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was not established by a previous survey.



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a USFS 3¼" aluminum capped pipe, cap marked per diagram, 22" in the ground, with a mound of stone to cap, from which:

- A fir, 23" in diam., bears N.43°21'W., 2.00', scribed "XBT".
- A fir, 15" in diam., bears N.57°57'E., 33.51', scribed "XBT".
- A pine, 9" in diam., bears S.1°56'E., 29.60', scribed "¼S3BT".
- A ½" rebar with an 1 1/2" diam. aluminum cap stamped LS 2058, bears S.79°45'W., 17.04'.

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY
SURVEYOR

Date Received 10/28/98
Date Filed 10/31/98
By R. Robinson, Deputy
File No. 113-1998R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald E. Stoll 9/98

OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Office of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)