


**CERTIFIED RECORD OF LAND CORNER
MONUMENTATION**



History of original corner establishment:

SURVEYED BY: W.B. BARR, 1885, CONTRACT NO. 516

80.23 Set a basalt rock 12 x 12 x 4. 8 ins.in ground for ¼ sec. cor. marked ¼ on the W. side, from which:

- A pine, 8 ins. diam., bears S.36°W., 7 lks. dist. mkd. ¼ S BT.
- A pine, 13 ins. diam., bears N.62°E., 30 lks. dist. mkd. ¼ S BT.

Description of corner evidence found:

No evidence of original monument found.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Ronald E. Stoll 9/98
OREGON
JULY 15, 1983
RONALD E. STOLL
2053

Description of monument and accessories I established to perpetuate the original location of this corner:

At a proportionate position, set a USFS 3 1/4" aluminum capped pipe, cap marked per diagram, 25" in the ground with a 24" mound of stone, from which:

- A pine, 6" diam., bears S.00°24'W., 50.33', with a 18" blaze, scribed "¼ S5 BT".
- A pine, 11" diam., bears N.82°45'E., 27.82', with a 18" blaze, scribed "¼ S4 BT".
- A pine, 12" diam., bears N.18°12'E., 27.17', with a 18" blaze, scribed "¼ S4 BT".
- A chiseled "x" in ledge rock 12' x 9' x 2' on North-East edge, bears S.62°27'W., 7.18'.

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____

(COUNTY OFFICIAL) by _____ (DEPUTY)

HENSON COUNTY
REGISTERED
DATE RECEIVED 10/28/98
DATE FILED 10/31/98
BY R. ROBINSON, DEPUTY
FILE NO. 117-1998R