

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

DIAGRAM
T 6 S R 41 E
C-W 1/16
S 1
LS 2058
1994

History of original corner establishment:

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a USFS 3 1/4" aluminum capped pipe, cap marked per diagram, 26" in the ground, with a mound of stone to cap.

A fir, 8" in diam., bears S.26°20'W., 22.0", scribed "CW1/16S1BT".
A tamarack, 3" in diam., bears N.42°30'E., 20.8', scribed "CW1/16S1BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: ERIC GREEN
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY
SURVEYOR
Date Received 10/28/98
Date Filed 10/31/98
By R. ROBINSON, DEPUTY
File No. 124-1998R

REGISTERED
PROFESSIONAL
LAND SURVEYOR
M. J. Stoll
OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)