

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-1

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

ORIGINALLY SURVEYED BY J. STONE, 1875
CONTRACT NUMBER 235

"SET A STONE 16X9X7 PER INSTRUCTIONS"



DIAGRAM

DESCRIPTION OF CORNER EVIDENCE FOUND:

NONE

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

AT THE POSITION DETERMINED BY SURVEY I SET A 2 1/4" ALUMINUM CAPPED ALUMINUM PIPE, 30 INCHES LONG, TOP OF PIPE IS 15" ABOVE GROUND SURROUNDED BY A MOUND OF STONE. A CARSONITE POST IS SET 1 FOOT NORTH OF MONUMENT.

FROM THE MONUMENT A 5/8" REBAR WITH YELLOW PLASTIC CAP MARKED "APA" BEARS:

- 1. N71°00'25"E 18.74 FEET
- 2. N20°43'06"W 39.83 FEET
- 3. S45°02'20"W 43.43 FEET
- 4. S39°13'38"E 38.10 FEET

I hereby certify that the above corner point was perpetuated as hereon described on

AUGUST 25, 2000
MICHAEL POSADA, OREGON PLS 02849

Witnesses: MIKE KIN KAID, SURVEY TECHNICIAN

D:\DOC\FORMS\CERTCORNON.mpd

UNION COUNTY
SURVEYOR

Date Received 8/24/00

Date Filed 8/24/00

By [Signature]

File No. 021-2000R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature]

OREGON
JAN. 20, 1898
MICHAEL B. POSADA
02849LS

EXPIRES 12-31-00

DATED 08-25-00