

E-9 T6S R41E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON Post 28" Long 24" IN Ground With
5' Steel Fence Post Alongside



ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A	w. Fir	18"	BRS.	N 24 1/2° E	38 LKS.	MKD.	T6S	R41E	S4 BT
A	w. LARCH	10"	BRS.	S 17° E	114 LKS.	MKD.	T6S	R41E	S9 BT
A	FIR	9"	BRS.	S 74° W	44 LKS.	MKD.	T6S	R41E	S8 BT
A	w FIR	16"	BRS.	N 72° W	312 LKS.	MKD.	T6S	R41E	S5 BT

Work Done By S. ALBRIGHT Title CADASTRAL SURVEYOR Date 10/6/71 State Registration No. or Agency RLS 838 BLM

Certified Cor. Record Prepared? Yes No Filed At: _____ Date _____

REMARKS

Index File No. T. R. M. Tract or Surv. No. Cor.

UNION COUNTY SURVEYOR

Date Received _____


Date Filed 12-23-87

By G. LANGLITZ, DEPUTY

File No. 380-87R

E-9

CERTIFIED RECORD OF LAND CORNER MONUMENTATION



History of original corner establishment:

SURVEYED BY: S. ALBRIGHT, 1971, CONTRACT NO. 350

The cor. of secs. 4, 5, 8, and 9, determined at record bearing from remaining original bearing trees:

A western larch snag, 11 ins. in diam., bears N. 70° E., 14 lks. dist., with scribe marks T6S 41E S4 BT visible on open double blaze. (Record, 11 lks.)

A sawed western larch stump, 17 ins. in diam., bears S. 35° E., 26 1/2 lks. dist., with scribe marks BT visible on open blaze. (Record, 14 lks.)

A white fir, 18 ins. in diam., bears S. 57° W., 16 lks. dist., with scribe mark 8 visible on open blaze. (Record, 16 lks.)

at the corner point

set an iron post, 28ins. long, 2 1/2" in diam., 24" in the ground, with brass cap

from which new bearing trees

- A white fir, 18 ins. diam., bears N.24 1/2°E., 38 lks. dist. mkd. T6S R41E S4 BT
- A western larch, 10 ins. diam., bears S.17°E., 114 lks. dist. mkd. T6S R41E S9 BT
- A fir, 9 ins. diam., bears S.74°W., 44 lks. dist. mkd. T6S R41E S8 BT
- A white fir, 16 ins. diam., bears N.72°W., 312 lks. dist. mkd. T6S R41E S5 BT

Description of corner evidence found:

Found a 3" BLM bass capped, cap marked per diagram, 6 " above the ground, with no stones, from which:

- A fir, 15" diam., bears S.22°41'E, 75.67', with a 24" healed blaze.
- A fir, 20" diam., bears S.10°11'W, 29.20', with a 15" healed blaze.
- A fir, 15" diam., bears N.73°52'W, 206.61', with a 24" healed blaze.
- A dead fir, 28" diam., bears N.64°27'E, 24.53', with a 19" healed blaze.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald E. Stoll 9/98

OREGON
JULY 15, 1933
RONALD E. STOLL
2058

Description of monument and accessories I established to perpetuate the original location of this corner:

A stump, 26" diam., 39 ins. high, with a 1/2" rebar set 6" above the middle of stump, with a aluminum cap bears N.85°05'W., 15.90'.

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

AG

UNION COUNTY
SURVEYOR
Date Received 10/28/98
Date Filed 10/31/98
By R. Roberson, Deputy
File No. 139-1998R

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

Set 5 ft. steel fence post alongside iron post.

(Remonumenting corners established by
William B. Barr, in 1885)

The corner of secs. 8, 9, 16 and 17, determined at record distance from the remaining original bearing trees:

A sawed ponderosa pine stump, 36 ins. diam., bears N. 27° E., 131 lks. dist., with scribe marks BT visible on open blaze. (Record, N. 22° E.)

A sawed ponderosa pine stump, 30 ins. diam., bears S. 58° W., 8 lks. dist., with scribe marks 4, S17 BT visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, directly over X marked on bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 6 S R 41 E

S 1 S 9

S 17 S 16

1941

from which new bearing trees

A fir, 12 ins. diam., bears N. 20° E., 66 lks. dist., mkd. T6S R41E S9 BT.

A ponderosa pine, 11 ins. diam., bears S. 12½° E., 102 lks. dist., mkd. T6S R41E S16 BT.

A ponderosa pine, 10 ins. diam., bears S. 37° W., 98 lks. dist., mkd. T6S R41E S17 BT.

A fir, 11 ins. diam., bears N. 19° W., 52 lks. dist., mkd. T6S R41E S8 BT.

The corner of secs. 4, 5, 8 and 9, determined at record bearing from remaining original bearing trees:

A western larch snag, 11 ins. diam., bears N. 70° E., 14 lks. dist., with scribe marks T6S 41E S4 BT visible on open double blaze. (Record, 11 lks.)

A sawed western larch stump, 17 ins. diam., bears S. 35° E., 26½ lks. dist., with scribe marks BT visible on open blaze. (Record, 14 lks.)

A white fir, 18 ins. diam., bears S. 57° W., 16 lks. dist., with scribe mark 8 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature]

File No. 297-2013R

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 41 E., Willamette Meridian, Oregon

HAINS

in the ground, with brass cap mkd.

T 6 S R 41 E
S 5 | S 4
3 | S 9
1971

from which new bearing trees

A white fir, 18 ins. diam., bears N. 24 $\frac{1}{2}$ ° E.,
38 lks. dist., mkd. T6S R41E S4 BT.

A western larch, 10 ins. diam., bears S. 17° E.,
114 lks. dist., mkd. T6S R41E S9 BT.

A fir, 9 ins. diam., bears S. 74° W., 44 lks.
dist., mkd. T6S R41E S8 BT.

A white fir, 16 ins. diam., bears N. 72° W.,
312 lks. dist., mkd. T6S R41E S5 BT.

Set 5 ft. steel fence post alongside iron post.

The corner of secs. 5, 6, 7 and 8, determined at record
distance from the remaining original bearing trees:

A sawed and rotted ponderosa pine stump,
24 ins. diam., bears N. 49 $\frac{1}{2}$ ° E., 70 lks.
dist., with illegible scribe marks visible
in open blaze. (Record, N. 45° E.)

A sawed and burned ponderosa pine stump, size
indeterminate, bears S. 63° W., 71 lks. dist.,
no marks visible.

A decayed ponderosa pine stump, size inde-
terminate, bears N. 55° W., 126 lks. dist.,
no marks visible.

At the corner point

Set an iron post, 24 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 6 S R 41 E
S 6 | S 5
7 | S 8
1971

from which new bearing trees

A ponderosa pine, 13 ins. diam., bears
N. 37° E., 6 $\frac{1}{2}$ lks. dist., mkd. T6S R41E
S5 BT.

A ponderosa pine, 14 ins. diam., bears
S. 12° E., 87 lks. dist., mkd. T6S R41E
S8 BT.

A ponderosa pine, 17 ins. diam., bears
S. 76° W., 42 lks. dist., mkd. T6S R41E
S7 BT.

A ponderosa pine, 14 ins. diam., bears
N. 76 $\frac{1}{2}$ ° W., 83 lks. dist., mkd. T6S R41E
S6 BT.

Set 5 ft. steel fence post alongside iron post.

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 397-2013R