

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

DIAGRAM
T 6 S R 41 E
S 3
¼ -----
S 10

LS 2058
1994

History of original corner establishment:

SURVEYED BY: W.B. BARR, 1885, CONTRACT NO. 516

39.85 Set stone 14 x 12 x 10 for ¼ sec cor, from which:

A fir, 30 ins. diam., bears S.65°W., 120 lks. dist.

Description of corner evidence found:

No evidence of original corner found.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
M. E. Stoll
OREGON
JULY 15, 1988
RONALD E. STOLL
2058

Description of monument and accessories I established to perpetuate the original location of this corner:

At a proportionate position, set a USFS 3 1/4" aluminum capped pipe, cap marked per diagram, 15" in ground with 2' mound of stone to cap (Corner falls on westerly slope) from which:

- A Fir, 8" diam., bears S.11°59'W., 107.81' scribed "X BT".
- A Pine, 11" diam., bears S.71°03'E., 57.25' scribed "X BT".
- A Pine, 10" diam., bears N.57°40'E., 40.52' scribed "1/4 S3 BT".
- A Pine, 13" diam., bears N.79°08'W., 44.06' scribed "1/4 S3 BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19__
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

LEWIS COUNTY
SHERIFF
Date Received 10/28/98
Date Filed 10/31/98
By R. ROBINSON, DEPUTY
File No. 132-1978R