

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM
T 6 S R 41 E
N W 1/16

S 10

LS 2058
1994

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald E. Stoll 9/98

OREGON
JULY 10, 1933
RONALD E. STOLL
2058

Set a 3" USFS aluminum capped pipe, cap marked per diagram, 22" in ground with 1' mound of stone. Corner falls on northeasterly slope \pm 35 SW of N&E fence corner, from which:

- A fir, 8" diam., bears N.2°39'E., 23.20' scribed "NW1/16 S10 BT".
- A fir, 8" diam., bears S.65°16'E., 21.22' scribed "NW1/16 S10 BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.


Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

AN

UNION COUNTY
REGISTERED
Date Received 10/28/98
Date Filed 10/31/98
By R. ROBINSON, Deputy
File No. 146-1978R

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

F-14



History of original corner establishment:

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a USFS 3 1/4" aluminum capped pipe, cap marked per diagram, 22" in ground with 1' mound of stone. Corner falls on northeasterly slope ± 35 SW of N&E fence corner, from which:

- A fir, 8" diam., bears N.2°39'E., 23.20' scribed "NW1/16 S10 BT".
- A fir, 8" diam., bears S.65°16'E., 21.22' scribed "NW1/16 S10 BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARING WAS GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY
SURVEYOR

Date Received 1/18/06

Date Filed 9/9/06

By R. ROBINSON, DEPUTY

File No. 010-2006R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

R. E. Stoll 6/04

OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 20 ____.

(COUNTY OFFICIAL) (DEPUTY)

AN