


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: W.B. BARR, 1885, CONTRACT NO. 516

40.00 Set stone 14 x 12 x 10. For 1/4 sec. cor., from which:

A tamarack, 24 ins. diam., bears N.60°E., 40 lks. dist.



Description of corner evidence found:

No evidence of original monument found.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald E. Stoll 9/1/98

OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Description of monument and accessories I established to perpetuate the original location of this corner:

At a proportionate position, Set a USFS 3/4" aluminum capped pipe 24" in the ground, with a mound of stone to cap, from which:

- A pine, 14" diam., bears S.05°17'E., 118.08', scribed "1/4 S10 BT".
- A pine, 16" diam., bears N.67°48'E., 110.78', scribed "1/4 S10 BT".
- A pine, 18" diam., bears N.49°54'W., 34.18', scribed "1/4 S 9 BT".
- A pine, 16" diam., bears S.35°46'W., 43.36', scribed "1/4 S9 BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
 WITNESS TO MONUMENT: DAVID SUTHERLAND
 BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
 BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ___ day of _____, 19___
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

AW

UNION COUNTY
 SURVEYOR
 Date Received 10/28/98
 Date Filed 10/31/98
 By R. ROBINSON, Deputy
 File No. 154-1998R