


J-21 T6S R41E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON Post 28" Long Set 24" IN GROUND  
with 5' steel Fence Post Along side



ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

- A P. Pine 13" BRs. N61 3/4° E 47 1/2 LKS, MKD, T6S R41E S12 BT
- A P. Pine 13" BRs. S31° E 56 1/2 LKS, MKD, T6S R41E S13 BT
- A P. Pine 7" BRs. S71 1/2° W 119 LKS, MKD, T6S R41E S14 BT
- A P. Pine 12" BRs. N67° W 85 LKS, MKD, T6S R41E S11 BT

Work Done By S ALBRIGHT Title CADASTRAL SURVEYOR Date 10/1/71 State Registration No. 265838 or Agency BLM

Certified Cor. Record Prepared? Yes  No  Filed At: \_\_\_\_\_ Date \_\_\_\_\_

REMARKS

Index File No. \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ M. \_\_\_\_\_ Tract or Surv. No. \_\_\_\_\_ Cor. \_\_\_\_\_

**UNION COUNTY  
SURVEYOR**

---

Date Received \_\_\_\_\_


Date Filed 12-23-87

By G. LANGLITZ, DEPUTY

File No. 385-87R

J-21

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**



**History of original corner establishment:**

SURVEYED BY: W.B. BARR, 1885, CONTRACT NO. 516

SURVEYED BY: S. ALBRIGHT, 1971, CONTRACT NO. 350

The cor. of secs. 11, 12, 13, 14, determined at record bearing and distance from the only remaining original bearing tree:

A sawed ponderosa pine stump, 42 ins in diam., bears S. 70° E., 57 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap

from which new bearing trees

- A ponderosa pine, 13 ins. diam., bears N.61 3/4°E., 47½ lks. dist. mkd. T6S R41E S12 BT.
- A ponderosa pine, 13 ins. diam., bears S.31°E., 56½ lks. dist. mkd. T6S R41E S13 BT.
- A ponderosa pine, 7 ins. diam., bears S.71½°W., 119 lks. dist. mkd. T6S R41E S14 BT.
- A ponderosa pine, 12 ins. diam., bears N.67°W., 85 lks. dist. mkd. T6S R41E S11 BT.

**Description of corner evidence found:**

Found a BLM 3" diam. brass capped pipe, cap marked per diagram, 6" above the ground from which:

- A ponderosa pine, 14" diam., bears N.65°17'W., 55.90', with a 26" x 3" blaze (not legible).
- A ponderosa pine, 24" diam., bears S.71°34'W., 78.27', with a 24" healed blaze.
- A ponderosa pine, 16" diam., bears S.32°10'E., 36.64', with a 18" healed blaze.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

A ponderosa pine, 14" diam., bears N.87°42'E., 84.47', with a 18" x 4" blaze, scribed "T6S R41E S12 BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY  
 WITNESS TO MONUMENT: DAVID SUTHERLAND  
 BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.  
 BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY SURVEYOR
Date Received <u>10/28/98</u> Date Filed <u>10/31/98</u>
Office of <u>R. Robinson Deputy</u> County of _____ State of _____ I hereby certify that the within instrument was filed in this office for record on the <u>16</u> day of <u>1998</u> , 19____ by _____

REGISTERED PROFESSIONAL LAND SURVEYOR  <i>R. E. Stoll</i> OREGON JULY 15, 1983 RONALD E. STOLL 2058
---

(COUNTY OFFICIAL)

(DEPUTY)



T6S 41J21

## T. 6 S., R. 41 E., Willamette Meridian, Oregon

## CHAINS

The following field notes describe the remonumentation of certain original corner points, township 6 south, range 41 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350 Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivision, T. 6 S., R. 41 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by John W. Stone,  
in 1875)

The cor. of secs. 11, 12, 13, and 14, determined at record bearing and distance from the only remaining original bearing tree:

A sawed ponderosa pine stump, 42 ins. diam., bears S. 70° E., 57 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 41 E  
S 11 | S 12  
S 14 | S 13  
1971

from which new bearing trees

A ponderosa pine, 13 ins. diam., bears N. 61½° E., 47½ lks. dist., mkd. T6S R41E S12 BT.

A ponderosa pine, 13 ins. diam., bears S. 31° E., 56½ lks. dist., mkd. T6S R41E S13 BT.

A ponderosa pine, 7 ins. diam., bears S. 71½° W., 119 lks. dist., mkd. T6S R41E S14 BT.

A ponderosa pine, 12 ins. diam., bears N. 67° W., 85 lks. dist., mkd. T6S R41E S11 BT.

Set 5 ft. steel fence post alongside iron post.

Corner falls at intersection of old fences, extending N., S., and E.

The cor. of secs. 9, 10, 15, and 16, monumented with the original basalt stone, 20 x 8 x 6 ins., loosely set 4 ins. in the ground, marked with 3 grooves on E. face and 4 notches on S. edge, from which the original bearing trees:

A root hole, bears N. 32° E., 80 lks. dist., with a down ponderosa pine alongside, size indeterminate, no marks visible. (Record, N. 40° E.)

T6S 41 J21

T6S 41 J21

UNION COUNTY  
SURVEYOR

Date Received

3/15/13

Date Filed

3/15/13

By

J. S. Woodruff

File No.

401-2013R