


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

ORIGINAL SURVEY BY JOHN W. STONE,  
UNDER CONTRACT NO. 235, JULY, 1875:

SET STONE 14 X 12 X 10 FOR 1/4 SEC. COR.



NOTE: AT 1.50 CHAINS SOUTH OF 1/4 LOCATION,  
ORIGINAL NOTES CALL FOR A "BLUFF".

Description of corner evidence found:

FOUND A BASALT STONE, 23" X 6" X 4" LYING LOOSE IN A MOUND  
OF STONE APPROX. 3 FT. DIAMETER, WITH DISTINCT CHISEL MARKINGS  
" 1/4 " .

STONE IS LOCATED APPROX. 100 FT. NORTH OF A ROCK BLUFF AND  
30 FT. WEST OF A N-S FENCING IN OPEN SAGEBRUSH - GRASS  
RANGELAND .

STONE LOCATION AGREES WITH ORIGINAL TOPOGRAPHY CALLS  
AND WITH GENERAL LOCATION ON U.S. GEOLOGICAL TOPOGRAPHY MAPS.

~~Description of monument and accessories established to perpetuate the  
original location of this corner:~~

STONE SIZE IS SUBSTANTIALLY DIFFERENT THAN ORIGINAL CALLS.  
A SMALL GROWTH OF LICHEN IS PRESENT IN THE CHISELED AREA  
OF THE STONE MARKINGS. NO ADDITIONAL EVIDENCE WAS FOUND  
IN THE VICINITY, ALSO, NO ADDITIONAL INFORMATION WAS FOUND  
IN THE UNION COUNTY RECORDS.

NO MONUMENT ESTABLISHED AT THIS TIME.

JULY 26, 1984

GARY LANGLITZ, DEPUTY  
UNION CO. SURVEYOR

DAVE DAHLSTROM, U.S.F.S.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Gary Langlitz*  
OREGON  
JULY 22, 1977  
GARY L. LANGLITZ  
1099

UNION COUNTY  
SURVEYOR

Date Received 8-27-84

Date Filed 8-27-84

By G. LANGLITZ, DEPUTY

File No. 934-84 R

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

..... by .....

(COUNTY OFFICIAL)

(DEPUTY)