


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was originally established by W.B. BARR, U.S. Deputy Surveyor, under Contract No. 443, dated May 29, 1882. Surveyor General records state:
Set a stone 12"X 10"X 6", marked with 1/4 on the W. side, from which:
A 3" fir bears S 36½° W - 36 lks dist.
A 16" pine bears N 40° E - 60 lks dist.



See Survey 052-1994

Description of corner evidence found:

Found a stone 6"X 9"X 12" marked 1/4 from which:
A 15" pine stump bears N 40° E - 39.6 feet with visible axe marks.

Description of monument and accessories I established to perpetuate the original location of this corner:

At postion of the found stone:

Set a 2½" X 30" aluminum pipe with a 2½" aluminum cap, 24" in ground and surrounded with a mound of earth and stone. Deposited stone in hole along side of monument.

Attached sign 54-9 to steel fence post, set 3.5 feet North of monument.

New bearing trees established:

- A 18" douglas fir bears N 27° W - 30.4 feet, scribed: 1/4S18BT.
- A 14" douglas fir bears N 12½° E - 26.3 feet, scribed: 1/4S17BT.
- A 10" ponderosa pine bears S 75½° W - 10.8 feet, scribed: 1/4S17BT.
- A 10" western larch bears S 78½° W - 3.2 feet, scribed: 1/4S18BT.

New bearing trees have a brass washer stamped "PLS 1106" nailed to face of blaze. Attached sign 54-3 & 54-9, painted face of blaze & a 6" red band around each bearing tree.

I hereby certify that the above corner monument was properly monumented to U.S.F.S standards by me on December 1, 1993.

Compass declination 18° East.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

renews 12-31-94

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of.....

(COUNTY OFFICIAL)

(DEPUTY)

UNION COUNTY
SURVEYOR

by _____

Date Received 11/3/94

Date Filed 11/14/94

By Greg T. Blake

File No 152-1994R

Form R6-7100-57 (9/71)