


Index File No. N 13 CORNER RECORD (SEARCH) (Ref. FSM 7151.4) Tract or Survey No. _____ Cor. No. _____
 T 6 S R. 42 E R.D. UNION County UNION BRACK
 Merid. W-M N.F. W-W State OKC

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

SMALL STONE MOUND NO MARKINGS ²

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

28" PP IN SEC 21 WITH UPPER SCAR CHOPPED AND BURIED OUT. LOWER SCAR GROWN OVER F.S. LOCATION POSTER NAILED TO TREE TAG IS RUSTED CANNOT READ DF. STUMP IN SEC 15 THAT FITS NOTES ³
 LARGE ROTTEN PINE IN SEC 22 THAT FITS NOTES ³

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

PHOTO IDENTIFICATION DATA

Photo No. 819170
 Filed At. FO21-117
 Object Ident. _____
 Ident. By _____
 Signature _____ ⁷

PLANE COORDINATE POSITION DATA

State _____ Zone _____
 X _____
 Y _____
 Estab. By _____
 Agency _____ ⁸

Signature EWH Title _____ Division _____ Headquarters _____ Date 9/6/78 7100-52-(3, 68) ⁴ ⁵

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-23-87

By G. LANGLITZ, DEPUTY

File No. 407-87R

N-13

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

N-13

History of original corner establishment:


80.00 Set basalt rock 16 x 12 x 3 ins., 11 ins in the ground for corner to sec. 15, 16, 21, and 22, marked with 3 notches on the East and 3 notches on the South, from which:

A fir, 5 ins. diam., bears N.28°E., 113 lks. dist. mkd. T6S R42E S15 BT.

A pine, 16 ins. diam., bears S.72°E., 198 lks. dist. mkd. T6S R42E S22 BT.

A pine, 10 ins. diam., bears S.47°W., 75 lks. dist. mkd. T6S R42E S21 BT.

A fir, 12 ins. diam., bears N.33°W., 190 lks. dist. mkd. T6S R42E S16 BT.



Description of corner evidence found:

Found a small mound of stone, from which:

A dead and down pine, 32" diam., bears S.45°20'W., 50.11', scribing not visible.

A pine stump, 24" diam., bears S.65°28'E., 134.92', blaze not visible

A fir stump, 24" diam., bears N.28°00'E., 74.6'.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 3" diam. U.S.F.S aluminum capped pipe, 30" long, with magnet, 2" in ground at location of found small mound of stone, from which:

A pine, 11" diam., bears N.38°26'W., 56.97', scribed "T6S R42E S16 BT".

A fir, 13" diam., bears S.56°22'W., 22.74', scribed "T6S R42E S21 BT".

A pine, 19" diam., bears S.59°55'E., 60.61', scribed "T6S R42E S22 BT".

A fir, 18" diam., bears N.28°09'E., 52.96', scribed "T6S R42E S15 BT".

UNION COUNTY SURVEYOR	
Date Received	<u>8/18/94</u>
Date Filed	<u>10/23/94</u>
By	<u>Greg T. Clark</u>
File No.	<u>041-1994R</u>



Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the _____ day of _____, 19____

_____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

Z

N-13