## **CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

0-8

History of original corner establishment:

DIAGRAM T 6 S R 42 E

SE 1/16

S 20

LS 2058 1992

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 3" diam. U.S.F.S aluminum capped pipe, 30" long, with magnet, 24" in ground with mound of stone to cap, from which:

A pine, 12" diam., bears N.73°55'E., 9.42', scribed "SE1/16 S20 BT". A pine, 10" diam., bears S.24°46'E., 24.46', scribed "SE1/16 S20 BT".

40 m mm m m	VEYOR	ITY	
DUM	AELOM	a Recognitive supplies in manuscriptures	
Date Receive	8/18	194	
Date Filed /			beginnen odderden
00		dera	
Ву	1-15-	minima innemitati	
File No.	1 -100	10	and an artist

K

PROFESSIONAL PROFESSIONAL PROPESSION ALL PROPESSION AND SURVEYOR CANDOL SURVEY

Office of			County of			
State of		I hereby certif	y that the within	instrument v	vas filed in	a this office
for record on the	day of		, 19			
		by				
(COUNTY O	FFICIAL	)	(DEPUTY)			