


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

37.71 Set basalt rock, 24 x 12 x 4 ins. 8 ins in the ground, for  $\frac{1}{4}$  corner Sec. corner marked  $\frac{1}{4}$  on the North side, from which:

- A fir, 14 ins. diam., bears S.46°W., 40 lks. dist. mkd.  $\frac{1}{4}$  S BT.
- A fir, 10 ins. diam., bears N.34°W., 31 lks. dist. mkd.  $\frac{1}{4}$  S BT.



**Description of corner evidence found:**

**Description of monument and accessories I established to perpetuate the original location of this corner:**

No evidence of original monument. Set a 3" diam. U.S.F.S aluminum capped pipe, 30" long, with magnet, 20" in ground at proportional position with mound of stone to cap, from which:

- A tamarack, 10" diam., bears N.45°02'W., 11.42', scribed " $\frac{1}{4}$  S21 BT".
- A fir, 6" diam., bears S.78°45'W., 19.38', scribed " $\frac{1}{4}$  S28 BT".
- A tamarack, 6" diam., bears S.19°37'E., 12.65', scribed " $\frac{1}{4}$  S28 BT".
- A tamarack, 9" diam., bears N.63°20'E., 6.03', scribed " $\frac{1}{4}$  S21 BT".

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 15 1983  
RONALD E. STOLL  
2058

**UNION COUNTY SURVEYOR**

Date Received 8/18/94

Date Filed 10/22/94

By [Signature]

File No. 038-1994R

Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)