Index File No.	COMMENT MEDOMO (COMMENT)	Tract or Survey No.	Cor. No	
T 65 R. 425	R.D. HALDA County DAY	20		
Merid. Willamer	N.F. W. W. State OK	E90N _		
DRNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND			
	ROCK PAINT - Set fi	form Notes	of Bearing	
29 , 28	TREES.			
20 27	BASALE ROCK 11 18 110	11" in ground		
	4 noteles or East			
1 30	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND			
32 33	2 Wall MARKED BEARING T	REES / BOOK	V0	
	2 Wall MARKED BEARING TO 1 P.P. 54" DIAM	Table	TARES	
	1 P.P. 40" DIAM	(MY 7/4) +	PAINTED -	
	BEARING TREE DOWN, SCR	thing Visible		
PHOTO IDENTIFICATION DATA				
Photo No. EN W - 8 - 243	I P.P. Stump Titte Bearing 1	vite (MOSCRION	().	
Filed At. U.R.D.			70 05 404 000450	
Object Ident. Pin Punched				
Ident. By H. F. F. & C.D. L.	MEATEL LINE TAG	OA ROAC	566	
PLANE COORDINATE POSITION DATA		. 70		
State Zone				
X				
Υ				
Estab. By	8			
Signature	Title Division Headqua	rters Date	7100-52	

UNION	COUNTY
SURV	EYOR

Date Filed 12-23-87

By G. LANGLITZ DEPUTY

File No. 420-87R


RECORD OF LAND CORNER MONUMENTATION

NORTHWEST CORNER SECTION 33, T. 6 S., R. 42 E., W.M.

ORIGINALLY ESTABLISHED BY: William B. Barr, U.S. Deputy Surveyor

CONTRACT NUMBER: 443

CONTRACT DATE: May 29, 1882



ORIGINAL DESCRIPTION: Set basalt rock 16x12x10, 11 inches in ground for corner to Sec 28, 29, 32, 33 marked with

- 4 notches on the East and 1 notch on the South edges, from which
- a pine 48 in diam bears S73°E 26 lks dist marked T6S R42E S33 B.T.
- a pine 18 in diam bears S81°W 112 lks dist marked T6S R42E S32 B.T.
- a pine 22 in diam bears N40°W 147 lks dist marked T6S R42E S29 B.T.
- a pine 22 in diam bears N4°E 190 lks dist marked T6S R42E S28 B.T.

EVIDENCE FOUND: Found a 2½" aluminum pipe with a 2½" Bagett-Griffith and Associates aluminum cap in a mound of stone and four bearing trees established in 1989 by Greg Blackman, PLS 991. I also found the original marked corner stone, which was buried North and alongside the pipe. The stone measured 16"x12"x10" and was marked with 4 grooves on one face and 1 groove on adjacent face. I also found the remains of the original northwest bearing tree, which is a 30" diameter ponderosa pine sawn stump, 6 feet tall, containing a blaze with fragmentary scribing, located at G.L.O. record bearing and distance from the aluminum monument. Although I find no record of the 1989 remonumentation in the county surveyor's records, it is obvious that Mr. Blackman's work represents a careful and faithful perpetuation of the original corner position, and I accept it for the section corner.

DESCRIPTION OF MONUMENTS AND ACCESSORIES SET AND METHODS USED:

From the found aluminum monument, marked as shown below, I found the following bearing trees marked by Blackman in 1989:

- ► A ponderosa pine 20" dbh bears N.30°E., 24.29 ft., with healed double blaze
- ► A ponderosa pine 23" dbh bears S.31°E., 31.42 ft., with healed double blaze
- ► A ponderosa pine 18" dbh bears S.49°W., 48.30 ft., with healed double blaze
- ► A ponderosa pine 19" dbh bears N.73°W., 24.3 ft., with healed double blaze

CORNER MONUMENT MARKED:



Replaced original corner stone alongside the aluminum pipe and repaired the mound of stone. Painted a 6 inch red band around each bearing tree, and also painted blazes red and attached USFS 54-3 and 54-9 signs. Bearings to BT's measured with a magnetic compass with 14° East declination. Distances were measured with a steel tape, measuring to a spike found in the side-center-right at the root crown of each tree. Also set an aluminum guard post East, 2.5 ft., with USFS 54-2 and 54-9 signs attached.

RESTORATION BY, STAMP AND DATE:

Work Performed July 20, 2022 by:

Jason L. Hatfield, PLS Daniel B. Lee

USDA FOREST SERVICE NORTHEAST OREGON LAND ZONE 1550 Dewey Avenue, Suite A Baker City, OR 97814 (541) 523-1283 UNION COUNTY
SURVEYOR

Date Received 12/14/22

Date Filed 12/14/22

By 12/14/22

File No. 038-7020

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
NOVEMBER 30, 2007
JASON L. HATFIELD
#69454

EXPIRES: 6/30/2023