CERTIFIED RECORD OF LAND CORNER MONUMENTATION

| | 하는 마음에 교육하는 100 ft 10kg 이 전쟁 이 하는 10kg 10kg 10kg 10kg 10kg 10kg 10kg 10kg | Index File No. Z-21 |
|---|---|-----------------------|
| | History of original corner establishment: Corner established in 1881 by Eugene P. McCornack under Contract No. 398. | DIAGRAM |
| | by Eugene F. McColliack under Contract No. 398. | R35 1/2E T6S |
| | A 16x20x5 stone was set, from which: | 35 36 |
| | a 10" Pine bears N40°E, 80 lks., a 6" Pine bears S20°E, 103 lks., | 2 1 T7S |
| | a 12" Tamarack bears S40°W, 42 lks., and | |
| | a 12" Tamarack bears N45°W, 46 lks. | |
| | | UNION COUNTY |
| | | SURVEYOR |
| | | Date Received 6-19-86 |
| | | Date Filed 6-19-86 |
| | [문화 등 경기] : 이 이번 사람 바다시아 보다 여러는 아니라 이 나는 것이다. 이 사람 | |
| | Description of corner evidence found: Found original stone with grooves in mound of stones. | BY G. LANGLIE LEPUTY |
| | | File No. 91-86 R |
| | BT's found: 12" L. Pine, good condition, bears N45°E, 80 lks, or | pen blaze. |
| | scribing visible: T6S R35 1/2E S36 BT (original notes say N40°E) | |
| 12" L. Pine, dead & down, bears S20°E, 103 lks, open blaze, faint scribing visible: T7S R35 1/2E S1 BT. | | blaze, |
| | 24" W. Larch, good condition bears S40°W, 42 lks, blaze healed. | |
| | 16" W. Larch, good condition bears N45°W, 46 lks, blaze healed. | |
| | | |
| | | |
| | | |
| | Description of monument and accessories established to perpetuate the Cap is stamped: T6S R35 1/2E | |
| | original location of this corner: | S35 S36 |
| | Set 2.5"x30" aluminum capped aluminum pipe rising 6" in mound of stones. Buried | S2 S1 |
| | original stone along north side of corner. | T7S |
| | Set steel fence post 3 ft. north of corner. | RLS 1848 1986 |
| | BT Set: | 1980 |
| | 10.5" W. Larch bears S66 1/2°E, 106.0 ft., blazed & scribed: T7SR351/2ES1BT | |
| | Attached 3/4" brass washer marked LS 1848 to blazes. Painted blazes | |
| | and attached signs as per Standard Specifications for Cadastral Surveys, | |
| | USFS Region 6, March 1982. | |
| | To find corner: A 14" D. Fir on the east side of 5100 | |
| | north of 5182 at the top of cut slope; corner is 520 gentle westerly slope. | ft. east on a |
| | | |
| | Compass Declination: 19 1/2°E Witness: J. Sutton | REGISTERED |
| | | PROFESSIONAL |
| | I hereby certify that the above described corner monument and/or accessories was | LAND SURVEYOR |
| | perpetuated as hereon described on June 6, 1986. | Stallow |
| | | OREGON |
| | | B. A. SUTTON |
| | | 1848 |
| | | |
| | Office of | |
| | State of, hereby certify that the within instrument was filed in a for record on the day of | unis office |
| | | |

(COUNTY OFFICIAL)

(DEPUTY)