


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. G-09

History of original corner establishment:

On the auxiliary meridian this Original corner established in 1881 by Eugene P. McCornack under contract #398. He set a stone, 20"x14"x10", 14" in ground. From which:
A 10" Pine bears N20°W, 32 Lks.
A 10" Pine bears S50°E, 11 lks.



Description of corner evidence found:

Found original stone, in place, broken, no marks.
Found the following original bearing trees:
At N20°W, 32 lks., found root hole with decayed remains of pine, no marks.
At S50°E, 11 Lks., found root hole & charred slab with axe marks and portion of BT visible.

Description of monument and accessories I established to perpetuate the original location of this corner:

Cap is stamped:

At the position of the original stone, I set a 2½"x30" aluminum capped aluminum pipe rising 7" in a mound of stones.
Set steel fence post 3' North.

T7S R35½E
|
¼S9
RLS1848
1987

New BT's:

A 6" Lodgepole Pine bears N45½°E, 15.4 ft., blazed&scribed: ¼S9BT
A 7" Lodgepole Pine bears S59¼°E, 10.6 ft., blazed&scribed: ¼S9BT

Painted blazes and attached signs as per Standard specifications for Cadastral Surveys, USFS Region 6, March 1982. A ¼" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

Go to the log landing at the end of 5182055. The SE corner of S12, T7S, R35E is visible at the NW corner of the clearing. Corner is ¼ mile due north in dense lodgepole thicket on gentle easterly slope.

Compass declination = 20½°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on June 25, 1987.



UNION COUNTY SURVEYOR

Date Received 8-19-87
Date Filed 8-24-87
By G. LANGLITZ, Deputy
File No. 69-87R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)