

T7S35 1/2 J09

Remonumentation of Certain Original Corner Points,
T. 7 S., R. 35 1/2 E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top with brass cap mkd.

T 7 S
R 35 E | R 35 1/2 E
S 13 | S 13
1974

from which new bearing trees

A lodgepole pine, 10 ins. diam., bears S. 70° W., 15 lks. dist., mkd. 1/2 S13 BT.

A lodgepole pine, 8 ins. diam., bears S. 17° W., 12 lks. dist., mkd. 1/2 S13 BT.

(Remonumenting a corner established by Eugene P. McCormack, Deputy Surveyor, in 1882)

The cor. of secs. 9 and 16 only, on the W. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

A lodgepole pine, 11 ins. diam., bears S. 35° E., 31 lks. dist., with scribe marks T7S R35 1/2 E S16 BT visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

T 7 S | T 7 S
R 35 E | S 9
S 13 | S 16
R 35 1/2 E
1974

from which a new bearing tree

A lodgepole pine, 6 ins. diam., bears N. 36° E., 15 lks. dist., mkd. T7S R35 1/2 E S9 BT.

Subdivision, T. 7 S., R. 35 1/2 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by W. B. B... Deputy Surveyor, in 1884)

The 1/4 sec. cor. of secs. 11 and 22, monumented with the original basalt stone, 22 x 10 x 10 ins., firmly set 6 ins. in the ground, mkd. 1/4 on W. face, from which the remains of the original bearing trees:

A decayed lodgepole pine stump, size indeterminate, bears N. 85° E., 39 lks. dist., no mark visible.

A lodgepole pine snag, 14 ins. diam., bears S. 88° W., 54 lks. dist., with scribe marks 1/4 S BT visible on open double blaze. (Record, S. 85° W.)

7S 35 1/2 J09

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 5/15/13

By [Signature] DEPUTY

File No. 402-2013R