

BRASS CAP
9 10
16 15

N 89-57-36 E
2684.08'

CONCRETE NAIL
1/4 CORNER 10
15

FOUND CONC. NAIL
21.55 N & 24.48 W
OF SET CORNER
(HISTORY UNKNOWN)

3 2
10 11
6 12
15 14

S 0-26-51 E
10,577.13'

CONCRETE NAIL
OVER CORNER
STONE
12 7
13 18

PIN SET .15 SOUTH AND .26 EAST
OF TRUE POSITION
(FENCE POST AT TRUE POSITION)

S 89° 49' 34" W
422.63

N 75° 48' 05" W
492.49

LIVESTOCK
COMMISSION

9.77 ACRES

3609.24'
N 2°-05'-12 E

321.55
S 18° 36' 08" E

3680.46
S 00° 10' 53" E

5339.50

131.90
S 51° 13' 48" E

ML 30+92.93 PSC

5331.31'
S 0-04-18 E

S 0-55-24 E
5327.90'

U.P.R.R.
HIGHWAY

1240.63
S 48° 24' 05" E

S 48° 24' 05" E

30

MAINLINE

00° 50' 45"
LC: N 02° 11' 44" E
8457'

180.05
S 89° 47' 07" E

OREGON STATE
HWY. DEPT.
34 ACRES

CURVE DATA
ML
1° CL
TA = 7° 00'
TS = 450.45
200' SPS.
S = 1° 00'
A = 0.5

MC ALISTER

ML 35+92.93 PCS

ML 37+92.93 P.T.

BASIS OF BEARING

FORWARD BEARING AS PUBLISHED
BY THE U.S.C. AND G.S. FROM
△ COLLEGE TO △ VALLEY

REFERENCE MATERIAL

OREGON STATE HIGHWAY DEPARTMENT MAP NUMBERS:
6-B-35-9
8-B-36-4

SURVEY NUMBERS:
37-71 10-72
76-71 40-72
89-71 67-73
7-72 1-74
9-72 24-75



LEGEND

- FOUND MONUMENT OF RECORD
- SET 5/8" x 30" IRON PIN WITH PLASTIC CAP MARKED B.G.A. SURVEY MARKER
- EXISTING FENCE LINE
- - - CENTERLINE ROAD & UNION PACIFIC TRACKS

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Gregory T. Blackman

OREGON
JULY 13, 1973
GREGORY T. BLACKMAN
991

BAGETT, GRIFFITH & ASSOCIATES
La Grande, Oregon

Map of Survey
LOCATED IN
THE NORTH 1/2 OF THE SW 1/4
SECTION 15, TWP 3S. R38E WM.
UNION COUNTY, OREGON

SURVEYED FOR	ROY POWERS	
SURVEYED BY	G.T.B.	5/77
Scale: 1" = 100'	Drawn by: S.S.Z.	5/77

CORNER POSITION BASED ON
ORE. STATE HWY. RECORD BEARING
FROM STA. 78 + 91.98 SURVEY NO. 37-71

FENCE CORNER
SURVEY NO.
37-71
16 15
21 22

2615.13
S 89-46-21 E

2619.82'
S 89-46-21 E
15 14
22 23

RAILROAD
SPIKE

43-77